

Never compromise on quality!



# **MONSTER TAPE**

## High Strength Water Resistant Tape



### TIGRIS TAPE RANGE

#### **Description:**

A high strength, water resistant, easy tear all purpose, heavy duty tape with high tack for binding, fixing, sealing, repairing, joining, protecting, marking and much more.

#### Uses

Rubber based adhesive provides long lasting adhesion on most substrates, and will adhere to rough surfaces.

Can be applied to wet and damp surfaces. Temporary (max. 5 hours) leak repair and water immersion. Will withstand short term water exposure e.g. rain showers.

Do not use on dusty or oily surfaces. It is the users responsibility to determine suitability of use.

#### **Application**

- **1.** Ensure surfaces are clean, free from dust and dry.
- 2. Remove outer packaging from roll of tape.
- **3.** Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
- 4. Cut with a knife or tear when finished.

#### Colour

Available in black.

Size

48mm x 11M rolls.

Shelf Life Maximum 5 years.

Storage Conditions

Store in cool, dry conditions.

#### **Disposal of Containers**

Do not leave unused product or discarded material on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.

#### Health & Safety

This product will cause no major hazard or problem to the users health.

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



#### **Specification Summary**

| Backing                 | PE laminated synthetic cloth |
|-------------------------|------------------------------|
| Adhesive                | Natural rubber               |
| Density                 | ca. 454g/m²                  |
| Thickness               | 420 microns +/- 10%          |
| Tensile Strength        | >180 N                       |
| Adhesion to Steel Plate | >5.5N/cm                     |
| Temperature Resistance  | ca. 2 hours @ 80°C           |

#### **Product Details:**

| Colour:   | Black      |
|---|------------|
| Code:   | BDWPT48    |
| Size:   | 48mm x 11M |
| Barcode: 5020021372505<br>Will be changing to 5056437400222 on<br>next re-print |            |



Part of the Bond It Tape Range



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



V3 15/02/21 Supercedes: V1 11/10/19



Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN. Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

#### BOND IT