

# S3 SANITARY SILICONE

## High Performance Sanitary Grade Silicone



### PREMIERE SILICONE & SEALANT RANGE

#### Description:

*A high performance, low maintenance, fungal resistant, waterproof silicone sealant. Conforms to EN 15651-1,3: 2012*

#### Uses

One part silicone sealant with excellent adhesion to ceramics, glass, melamine laminates and sanitary plastics. **S3 SANITARY SILICONE** is also compatible with anodised aluminium and lacquered metals. Bond It **S3 SANITARY SILICONE** contains a biocide to prevent unsightly mould growth.

Bond It **S3 SANITARY SILICONE** should be used for sealing around worktops, basins, sinks, bed basins to vanity units and also to seal shower trays and shower units. It has been specially designed to seal in damp and humid areas.

It is ideal for use on: glass; ceramics; anodised aluminium; lacquered and primed metals; painted timber and plaster; sanitary plastics; primed or painted concrete.

#### Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. Remove any old sealant.

#### Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed.

**For bath surrounds:** Half fill the bath with water to allow sealant to be applied at joint mid point. If necessary masking tape may be applied. If large gaps are to be filled, polythene foam, rod or tape should be used to provide support and minimise sealant wastage. Tool down within 5 minutes using a wet spatula or SEALANT APPLICATOR TOOL. Any trims should be bedded into the silicone within 5 minutes.



**For sealing waste outlets in sinks and baths:** **S3** should be applied so that it will be in compression after tightening of connecting pipes.

**For metallised plastic trims:** test for discolouration by sealant before use.

#### Limitations

Do not use on bare metal or fresh concrete without priming. Natural stone, particularly marble must be protected by primer/ sealer. Not suitable for mirrors. For fixing mirrors use Bond It LN7, MIRROR-MATE or MIRROR-PRO Hybrid Adhesive.



#### Colour

**S3 SANITARY SILICONE** comes in 3 colours: white, translucent and ivory.

#### Container Size

EU3 plastic cartridge.

#### Shelf Life

24 months from date of manufacture when stored in original unopened cartridges.

#### Storage Conditions

Store in cool, dry conditions at a temperature between 5 and 30°C.

#### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

#### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.**

Tooling Time	5-10 minutes
Skinning Time	15 minutes
Drying Time	1-2mm depth per day
Movement Capability	±20%

<b>Colour:</b>	Ivory	White	Translucent
<b>Code:</b>	BDS3IV	BDS3WH	BDS3T
<b>Size:</b>	EU3	EU3	EU3
<b>Barcode:</b>	5060021360472	5060021360496	5060021360489



CE

14

Facade sealant for exterior and interior use. Sanitary sealant.

Microbiological growth S1



**V5 25/02/16**  
*Supersedes: V4 20/08/14*