



SQUEEZE IT SAVES NAILS SF

Instant Grab Solvent-Free Adhesive



SQUEEZE IT SEALANT & ADHESIVE RANGE

Description:

An environmentally friendly, advanced technology formula offering instant grab and tough permanent bond on virtually any porous or non-porous surfaces.

A low odour, 99% VOC free, water clean-up construction adhesive. Cures to form a high strength bond. Contains no harmful raw materials, making it safer for the environment, safer for the user and safe on substrates.

Uses

Bond It **SQUEEZE IT SAVES NAILS SF** is ideal for adhering panelling, plasterboard, cove base, window sills, styrofoam, carpet tack strips, aluminium furring strips, tub surrounds, fireplaces, loose floor/wall tiles, plywood, aluminium, steel, wood, concrete, cork, general repairs to wood, fixing hardboard and plywood and as a general adhesive.

It is ideal for use on:

- plastics
- wood
- concrete
- brick
- plasterboard
- carpet
- metal.

Preparation

Ensure all surfaces to be bonded are clean, dry and free from grease or any contaminants that may hinder adhesion.

Application

Remove the cap and carefully cut the nozzle at an angle of 45° to an opening slightly larger than the gap to be sealed. Squeeze tube to extrude the sealant. Apply to one side only. Bring components together as soon as possible, pressing firmly and support for 24 hours. Remove excess product with water before drying. Replace the cap after use.

Limitations

Totally encapsulated joints will not dry completely. This adhesive should not be applied to asphalt, bitumen or on external damp or fully immersed locations. Do not use as a mirror adhesive. Do not use on two non-porous surfaces.

Container Size

EU2 plastic squeezy tube.

Colours

Available in white.

Shelf Life

12 months from date of manufacture when stored in sealed tubes.

Storage Conditions

Store in cool, dry conditions at a temperature between 5-15°C. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary	
Flammability	Non flammable
Application Temperature	5°C to 30°C
Service Temperature	-10°C to + 40°C
Consistency	Thick paste
Slump (ISO7390)	None

Product Details:

Colour:	White
Code:	BDSQSN2
Size:	EU2
Barcode:	5060021366597



Part of the Bond It Silicone & Sealants Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



BOND IT Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310

Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

