bond it

Never compromise on quality!

MADE IN THE UK

STAIN BLOCK

Fast Drying Coating for Covering Stains Prior to Painting



DECORATORS RANGE

Description:

A xylene and lead free, high performance, fast drying, pigmented solvent based permanent stain blocking coating. CFC Free.

Uses

For use prior to redecoration on spot marking, water marks and stubborn stains.

Suitable for interior use on most building surfaces including brick, plaster, paint and wood. We recommend the product be tested on a small inconspicuous area prior to application to determine suitability. When correctly applied **STAIN BLOCK** produces a fast drying, stain block coating ready for redecoration.

Preparation

Ensure all surfaces are clean, dry and free from grease or oil or any other contaminants that may hinder adhesion. Ensure the source of the stain has been eliminated. Mask off any areas that need protecting from spray and repair any holes, cracks or surface imperfections prior to coating.

Application

1. Ensure good ventilation whilst using this product. Shake can well until mixing ball rattles and continue to shake for a further 1-2 minutes. Shake frequently during use.
2. Spray directly and evenly over stain in a sweeping motion, 20-30 cm away from the stained area. The multi-directional nozzle in the horizontal position will produce a vertical line and vice versa.
3. Apply 2-3 coats dependant on stain. Allow to dry for at least 15 minutes before re-applying. Final decoration can commence approx. 2 hours after application. **Note:** ambient conditions and porosity of substrate will affect the drying times.
4. Store upright.

Drying Time

Do not apply at temperatures below 10°C or on substrates that have an RH reading of 90% or above.

Normally **STAIN BLOCK** should be touch dry after 15 minutes. Drying times are dependant on temperature, moisture content of the substrate and the area. In optimum conditions **STAIN BLOCK** will be ready for redecorating in approx 2 hours.

Coverage

One 400ml can covers 0.75m^2 dependent on the porosity of the substrate.

Container Size

400ml aerosol tin.

Colour

Off-white.

Shelf Life

2 years from date of manufacture.

Storage Conditions

Store in cool, dry conditions away from heat and out of direct sunlight. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Always store and transport in vertical position.

Disposal of Containers



Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce or burn canister after use.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner e.g. Bond It uPVC SOLVENT CLEANER.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Physical Form	Off-white viscous liquid
Flash Point	Less than -40°C
Solubility in Water	Immiscible
UFI	

Product Details:

Code:	BDSB400
Size:	400ml
Colour:	Off White
Barcode:	5060021369680



Part of the Bond It Decorating Sundries Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.

Certificate Number:
6152
ISO 9001
ISO 14001; ISO 45001

BOND IT
Head Office: *Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.*
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

V1 20/09/13
Supercedes: V