



Never compromise on quality!



# ANCHOR BOND

## Resin Mortar Anchoring System



### INDUSTRIAL GLUES & ADHESIVES RANGE

#### Description:

*A polyester resin, 2-part, rapid curing, chemical anchoring system. Applied in one single action to produce a cost effective, tough chemical resistant fixing.*

#### Uses

Suitable for setting bolts, studs, wall ties, starter bars or large screws, etc into a wide range of substrates. Compatible with brickwork, concrete, masonry, stone and PFA blocks. Hollow base materials can also be securely fastened using **ANCHOR BOND** in conjunction with a sleeve or sieve.

Chemically resistant, waterproof and vibration proof.

#### Preparation

Drill a hole to the correct diameter and depth (see chart over leaf), ideally using a rotary percussion machine. For optimum results the wall sides should be thoroughly roughened. Clean hole and remove all dust and debris using a hand air pump or a stiff rotary brush, if required.

All bars should be clean and free from oil or grease and all flaking rust should be removed. Threaded rods or studs should be chisel ended to prevent them being unscrewed from the cured resin.

#### Application

Screw the mixing nozzle on to the cartridge (hand tighten). Place the **ANCHOR BOND** cartridge into the dispensing gun. Squeeze the hand trigger a few times until material passes through the mixing nozzle. Allow the material to flow until an even colour is obtained (normally 5-6 inches). Insert the nozzle into the base of the hole and extrude material, half filling the hole with resin. Withdraw the nozzle then insert the fixing into the filled hole, slowly rotating to fully coat the surface. After application release the pressure from the dispensing gun. Remove the used mixing nozzle and wipe away excess material from the end of the cartridge. Once the resin has cured the fixture can be attached to the fixing and fully tightened. Do not over pressurise cartridge otherwise leakage may occur from rear pistons.

#### Curing

Dependant on temperature. As a guide @ 20°C:-

**Gel Time:** 5 minutes.

**Full Cure:** 2 hours.

#### Container Size

Available in 310ml and 400ml plastic cartridges with special mixing nozzle.

#### Colour

Grey in colour.

#### Shelf Life

12 months from date of manufacture when stored in unopened cartridges.

#### Storage Conditions

Store in a dry area between 5°C and 25°C. Keep out of direct sunlight. Storage at higher temperatures will reduce the shelf life.

#### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

#### Health & Safety

**Contains styrene.**

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.**



PERFORMANCE DATA AT STANDARD EMBEDMENT DEPTH IN 25N/MM<sup>2</sup> CONCRETE USING GRADE 8.8 STEEL

STUD SIZE (mm)	HOLE SIZE (mm)	HOLE DEPTH (mm)	RECOMMENDED LOAD (kn)	EDGE DISTANCE DEPTH (mm)	SPACING (mm)	MIN CONCRETE	APPROX NO OF FIXINGS/TUBE	
							380ml	310ml
M8	10	80	4.4	120	80	110	110	60
M10	12	90	7.9	135	90	120	60	40
M12	14	110	8.2	165	110	140	40	24
M16	18	125	12.6	190	125	170	20	16
M20	22	170	18.2	255	170	230	9	8
M24	26	180	27	275	210	260	-	-

GEL & CURE TIMES

Temp (°C)	Gel Time (Mins)	Min Load Time (Mins)
5	12	140
10	9	100
20	5	70
30	3	50

Product Details:

		ANCHORBOND GUN FOR 400ML CART	
Code:	BDAB380	BDAB310	BDABG3
Size:	400ml	310ml	400ml
Barcode:	5060021363541	5060021368669	5060021363992
UN Class	1866 Resin solution, flammable		
UFI	F140-P048-600X-G7RD		



Part of the Bond It Glues & Adhesives Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152  
ISO 9001; ISO 14001;  
ISO 45001



**BOND IT**  
Head Office: Unit G16 River Bank Way, Lowfields Business Park,  
Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 16/02/21  
Supersedes: V3 07/01/15