



Never compromise on quality!



DUCT TAPE

Water Resistant Duct Tape



TIGRIS TAPE RANGE

Description:

A water-resistant, all purpose, premium quality duct tape for binding, fixing, sealing, repairing, joining, protecting, marking and much more.

Uses

Rubber based adhesive provides long lasting adhesion on most substrates.

Do not use on wet or oily surfaces. It is the users responsibility to determine suitability of use.

Application

1. Ensure surfaces are clean, free from dust and dry.
2. Remove outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

Colour

Available in silver and black.

Size

48mm x 45M rolls.

Shelf Life

Maximum 5 years from date of manufacture.

Storage Conditions

Store in cool, dry conditions.

Disposal of Containers

Do not leave unused product or discarded material on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.

Health & Safety

This product will cause no major hazard or problem to the users health.

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Backing	PE laminated synthetic cloth
Adhesive	Synthetic rubber
Total Weight	approx 155gsm
Thickness	140 microns +/- 10%
MD Tensile Strength	>28N/mm
Adhesion to Steel Plate	>5.5N/cm
Rolling Back Tack	>0.5cm

Product Details:

Colour:	Silver	Black
Code:	BDDT45S	BDDT45BL
Size:	48mm x 45M	48mm x 45M
Barcode:	5056437400185	5056437400192



Part of the Bond It Tape Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001

BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V3 18/02/21
Supersedes: V2 10/06/16