

# bond it

Never compromise on quality!



# INDIAN STONE SEALER

## Solvent-Free Sealer for Protecting Natural Stone Patios



### DRIVE ALIVE RANGE

#### Description:

*A solvent-free advanced Fluoro polymer based formulation used to seal and protect patios particularly for high quality natural stone. Gives a high level of protection against water and oil penetration.*

#### Benefits:

- ◆ Solvent-free.
- ◆ Low odour.
- ◆ Improves water and oil resistance.
- ◆ Provides an easy clean surface.
- ◆ Helps prevent fungal and moss growth.

#### Uses

Protects patios, natural stone from water ingress from oil stains, particularly effective for protecting patios from fat spills and splashes from barbecues. **INDIAN STONE SEALER** does not affect the colour or appearance of your patio and gives durable highly effective protection.

#### Preparation

Remove organic growth/ lichens, etc. that may be present. For best results use Bond It MOULD STOP or PATIO BLASTER ; refer to the appropriate data sheet.

Wash all debris away and ensure the surface is dry and free from oil, grease, dust and loose material that may hinder adhesion.



#### Application

**INDIAN STONE SEALER** is ready to use, and does not require diluting. We advise that you test this product on a small inconspicuous area prior to use to check compatibility. **SHAKE WELL BEFORE USE.** Ensure that the surface is completely dry. Apply a single coat using either a brush, roller or squeegee, ensuring no pooling or ponding occurs. Allow 3-4 hours drying time before trafficking the area. Application temperature between 5°C and 30°C. Colder humid conditions will slow drying times.

#### Application Notes

It is necessary to seal paviours prior to the application of any pointing or jointing compound. Some compounds have the capability of staining porous paving materials. Ensure **INDIAN STONE SEALER** has completely cured prior to pointing. Do not apply **INDIAN STONE SEALER** to any uncured wet pointing or to any dry mix cement compound.

If applying **INDIAN STONE SEALER** to new paviours ensure a sufficient period of weathering (as recommended by the paving manufacturer) has elapsed in order to avoid efflorescence. Paviours can be resealed using a single coat of **INDIAN STONE SEALER**, if it is necessary. This can be determined by a small porosity test to the surface in an inconspicuous area. We suggest an area be subjected to a sprinkling of water via a watering can with rose attachment, if the water beads then a further application is not necessary as the seal is still intact. However, if the water is absorbed by the patio surface re-application can be performed. For patios with unknown treatments we would also suggest using the same test method to determine suitability. Adverse reactions can be caused if **INDIAN STONE SEALER** is used over other existing sealers or treatments so should be avoided at all times. Avoid over application in all circumstances.

#### Limitations

Do not apply **INDIAN STONE SEALER** to wet surfaces or in conditions of high humidity. Do not use when rain is forecast (protect from rain until dry). Keep children and pets away from treated areas until fully cured. Do not allow any run off to contaminate drains, waterways or plants. It is the users responsibility to determine suitability for use. If in doubt, consult our Technical Department for further details. Areas treated with this product can be cleaned with warm water and detergent or Bond It MOULD STOP. It is advisable to use this product during warmer/drier months (April to October). If oil or petrol is spilled on paving, clean up spill before penetration is allowed to occur (this will happen in time).

#### Container Size

5L plastic bottle.

#### Shelf Life

12 months from date of manufacture when stored in original sealed bottles.

#### Colour

Clear liquid.

### Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

### Coverage

4-8m<sup>2</sup> per litre.

### Cleaning

Rinse then wash brushes and rollers in warm, soapy water.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and

remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

*Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.*

### Specification Summary

Physical Properties	Clear liquid, non flammable, zero VOC, water miscible
Application	STIR WELL BEFORE USE Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	+5 to +30°C
Drying Time	1-2 hours in warm, sunny conditions
Coverage Rate	4-8m <sup>2</sup> per litre



### Product Details:

<b>Code:</b>	BDISS5
<b>Colour:</b>	Clear
<b>Size:</b>	5L
<b>Barcode:</b>	5056437400413

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*



Part of the Bond It Drive Alive Range



**BOND IT**  
 Head Office: Unit G16 River Bank Way, Lowfields Business Park,  
 Elland, West Yorkshire HX5 9DN.  
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com

