



Never compromise on quality!



PATINATION OIL

Protective Lead Surface Treatment



BUILDERS COMPLETE RANGE

Description:

A solvent based surface treatment for new lead sheet or flashings.

Uses

PATINATION OIL when correctly applied gives an evenness of colour to lead while its natural patina develops, it also prevents unsightly white staining.

Preparation

The lead to be treated should be clean, dry and free from cement, dust and loose debris that may affect adhesion.

Application

PATINATION OIL should be applied as soon as possible, immediately after each step of the lead work and certainly not later than the end of the working day. Lead must be completely dry before application of **PATINATION OIL**.

Apply at temperatures between 5°C and 35°C.

1. Shake the can vigorously for at least 2 minutes before use and occasionally during application.
2. Apply the oil with a soft absorbent cloth.
3. Work horizontally from top to bottom maintaining a wet lower edge. DO NOT USE A CIRCULAR SCRUBBING ACTION.
4. Ensure application is complete before any rain.

WARNING: cloths contaminated with **PATINATION OIL** should be burnt after use as in certain conditions spontaneous combustion can occur caused by oxidation of the oil.

Limitations

Do not allow **PATINATION OIL** to come into contact with bituminous surfaces or polycarbonate sheet.

Coverage

Approximately 60m² per litre.

Container Size

500ml and 1L plastic dosing bottles.

Colour

Straw coloured oil that dries clear once dry.

Shelf Life

24 months from date of manufacture when stored in unopened bottles.

Storage Conditions

Store in cool, dry conditions in a sealed container between 5 and 30°C.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Contains white spirit low aromatic.

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Appearance	Straw coloured liquid that dries clear
Flammability	Flammable
Boiling Point	152°C
Solubility in water	Insoluble
Flashpoint	38°C
UFI	6T10-H05X-8002-9CKQ

Product Details:

Colour:	Straw	Straw
Code:	BDPO05	BDPO1
Size:	500ml	1L
Barcode:	5060021367167	5060021367150



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001
ISO 14001; ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 20/05/20
Supersedes: V3 19/09/19