



Never compromise on quality!



# ROOF-MATE ROOF & GUTTER

## Lap Jointing Sealant

### Technical Data Sheet



#### MATE SEALANT & ADHESIVE RANGE

#### Description:

*A polymerically reinforced lap jointing sealant used to prevent leaks in gutters and downpipes.*

#### Uses

Bond It **ROOF & GUTTER MATE** is suitable for repairing and maintaining general roofing and roof drainage systems.

It forms a flexible seal capable of accommodating 5% movement. Remains flexible for up to 15 years.

It is ideal for use on: metal; construction grade plastics; paint; stone; brick; and bitumens.

#### Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion. Loose materials and signs of corrosion must be removed prior to application.

#### Application

Apply using a standard sealant gun. Cut tip from cartridge, be careful not to damage the screw thread. Cut the nozzle at an angle of 45° and fix to cartridge. Using a caulking gun force the sealant into the joint.

When a deep joint is being sealed a backing tape should be used.

After application any high spots of material should be feathered smooth to prevent water build up.

For emergency repairs in wet conditions Bond It RAIN-MATE should be used.

**ROOF & GUTTER MATE** maintains a permanently putty-like consistency. It is not suitable for applications where surface contact is likely.

Tools can be cleaned in WHITE SPIRIT or Bond It MULTI-WIPES prior to curing taking place.

#### Container Size

EU3 plastic cartridge.



#### Colours

Available in black.

#### Shelf Life

Minimum 2 years from date of manufacture when stored in unopened tubes.

#### Storage Conditions

Store in cool, dry conditions at a temperature between +5 to +30°C. Protect from frost.

#### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

#### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.**



## Specification Summary

Flammability	Flammable
Solubility in Water	Insoluble
Adhesion	Good to metals and plastics
Movement Value	5%

## Product / Order Details:

Code	Colour	Size	Barcode
BDGR	Black	EU3	5060021361608



Part of the Bond It Silicone & Sealants Range



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:  
6152  
ISO 9001; ISO 14001;  
ISO 45001



**BOND IT**  
Head Office: Unit G16 River Bank Way, Lowfields Business Park,  
Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: [salesuk@bonditgroup.com](mailto:salesuk@bonditgroup.com) Website: [www.bonditgroup.com](http://www.bonditgroup.com)



**V3 20/05/20**  
Supersedes: V2 19/09/11