

TECHNICAL DATA SHEET

BLACK BITUMINOUS PAINT

Issue 6 – December 2012

Description:

A solvent based, general purpose, bituminous black paint for waterproofing and weather protecting of steelwork, asphalt, wood and concrete. When dry it forms an odourless and taint-free bitumen film.

Cromar's Black Bituminous Paint forms a waterproof, weatherproof, corrosion resistant protective coating. It is resistant to low concentrations of alkalis and acids and can withstand prolonged oxidation.

It is suitable for application to a wide variety of surfaces including steel, iron, lead, zinc, aluminium, concrete, stone and brick but is mainly used for the following:-

Metal protection for any type of exterior metalwork – fire escapes, ladders, gutters etc.

A protective coating for concrete structures, stone, brick, concrete screeds and sand/cement surfaces.

Colour:

Black, shiny coating when dry - dulls with exposure to sunlight.

Container Sizes:

1, 2.5, 5 & 25

Coverage Rates:

The coverage per litre is dependent upon the porosity of the surface. For metal and smooth surfaces 10m² per litre per coat should be obtained. On porous surfaces coverage will be considerably less.

Method of Application:

By brush or airless spray, apply evenly and ensure no pooling of product. A minimum of two coats of Black Bituminous Paint is recommended.

Application Instructions:

All surfaces must be free from oil, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire brush and where advanced signs of corrosion are evident the area must be treated with a rust inhibitor. A minimum of two coats of Black Bituminous Paint should be applied, the first coat being allowed to dry before the second is applied.

On porous surfaces where the surface being treated is porous, an initial coat of Primer should be applied.

VOC Details:

EU Limit for this product CAT. 2(i) : 500g/l (2010). This product contains max. 400g/l VOC's

Storage Conditions:

Store away from children. Containers must be kept sealed and stored under cover away from sources of heat and ignition. Do not allow water to contaminate the product.

Storage Life:

Indefinite in undamaged, tightly sealed containers.

Cleaning Tools:

Tools may be cleaned with White Spirit. Minor spillages should be wiped off surfaces before the compound has set. Major spillages should be mopped up immediately with an inert, absorbent material, such as sand and disposed of in accordance with regulations.

Health & Safety:

Please refer to health & safety data sheet on Black Bituminous Paint

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com