

TECHNICAL DATASHEET

Vent3 Pro – Breathable Membrane

Description

Vent3 Pro is a triple layer fabric, high performance breather membrane, made from high tensile spun bonded polypropylene layers, around a micro-porous polypropylene film. Designed for use in a fully supported or unsupported tiled, slated or metal roof system. Superior moisture vapour permeability is achieved whilst maintaining the highest levels of water resistance. Vent3 Pro has a printed light green upper surface and white under-face.

The high vapour permeability and waterproof nature of the membrane, combined with excellent tensile/tear strength, make Vent3 Pro an ideal product for use in both warm and cold roof applications. Vent3 Pro is equally suitable whether draped unsupported over rafters or laid directly over insulation. It will allow the escape of water vapour from within the roof structure whilst protecting against wind driven rain, snow and dust which may penetrate the main roof waterproofing, providing a permanent quality breather underlay, which will last the life of the roof construction.

Benefits

- Three Layer Membrane
- Clean and easy to use
- Lightweight and Flexible
- Excellent tensile and tear strength
- Waterproof Membrane
- Long Term Durability
- UV Stable (3 months exposure)
- Warm and Cold Roof Application

Product Details

Roll Weight (kg)	4.5, 8.5, 12.5
Weight g/m²	165 (±10%)
Roll Length m	25, 50
Roll Width m	1 & 1.5
Roll Area m²	25, 50, 75
Colour	Light Green Upper / White Lower



Performance Details

Tensile Strength (EN13859-1)	MD 320N/50mm TD 270N/50mm
Elongation (EN13859-1)	MD 80 % TD 100%
Nail Tear (EN12310-1)	MD 290N TD 270N
Hydrostatic Head (BS EN 20811)	>100cm
Water (moisture) Vapour Transmission Sd (EN 12572)	0.02
Reaction to Fire (EN 13501-1)	Class E
Resistance to streaming water (MOAT69:4.2.2)	Pass
Resistance to water penetration (EN13859-1)	Class W1
UV Resistance	3 months

When tested in line with BS5534 2014 Annex A , Vent3 pro is suitable to be in the applications below and zones attached.

	345 mm batten gauge	245mm batten gauge	345mm gauge taped laps	345mm gauge integral tapes
Vent 3 pro	Zones 1 -4	All zones	All zones	All Zones

Application

Vent3 Pro must be installed in accordance with the relevant sections of BS 5534:2018 and Cromar's fixing instructions.

Vent3 Pro is designed as a secondary barrier to wind driven rain and snow, it should not be considered a primary waterproofing layer. Whilst the product is UV stable for up to 3 months exposure, good roofing practice dictates that the primary waterproofing finish (e.g. tiles, slates etc.) be applied as soon as practically possible.

Under slating membranes should not be considered as temporary weatherproof protection for occupied buildings or where internal fitting out is taking place. Additional protection should be afforded in these circumstances.

Vent3 Pro should be unrolled across the roof, starting at the eaves and working up the roof, it is usually laid Green (printed) side up. With normal slates and tiles the Vent3 Pro membrane should be installed to a maximum drape of 15mm into the void between the rafters in line with BS5534 2018. It can then be secured with the tiling battens. This will leave sufficient space between the Vent3 Pro and the tiles/slates for drainage and ventilation. Vent3 Pro when installed as a fully supported system, is laid over the support and secured with counter battens, alternatively the membrane can be installed over counter battens and fixed at 200mm centres using aluminium clout nails. Tiling battens are fixed to the counter battens leaving a minimum airspace of 25mm between the roof sheet underlay and the tiles for drainage and ventilation.

In unventilated roof systems vapour control measures are required below the insulation layer to restrict the flow of moist air from within the inhabited building into the roof space. Additionally, the building below should be ventilated in accordance with the Building Regulations with water tanks sealed.

At abutments Vent3 Pro underlay should be turned up behind the flashing at least 100mm to prevent rain and snow being blown into the roof-space. Lap joints in the membrane should be generally in accordance with the table set out below. 600mm reinforcing strips should be fixed at hips, ridges, and valleys.

At the eaves, Cromar felt support tray should be installed to prevent ponding behind the fascia. The Vent3 Pro should be laid over the support tray stopping short of the roof tile tails to prevent UV degradation of the underlay.

Notes

1. As with all breather membranes of this type, contact with solvents or wet timber preservatives can cause localised water penetration to occur, prior to the main weatherproofing being installed.
2. In accordance with BS 5534: 2018), where a roof underlay or breather membrane is to be laid over open rafters, a maximum drape of 15mm between the rafters is desirable to guide any rainwater penetrating the main roof finish away from the rafters to the drainage point. (The membrane must not be pulled tight against the underside of the tiling battens.)
3. Vent3 Pro should never be considered as being a total protection against wind-blown rain and high winds.
4. When laid with an impermeable primary barrier ventilation would be required in line with BS5250.
5. In line with the NHBC directive 2012 high level ridge ventilation of a continuous 5mm should be provided when using a VPU.

Lap Size Table

Roof Pitch	Minimum Horizontal Lap Partially Supported (mm)	Minimum Horizontal Lap Fully Supported (mm)	Minimum Horizontal Lap (mm)
12.5° - 15°	225	150	100
15° +	150	100	100

Limitations

- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited product' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.