according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING

Revision Date 04.08.2017 Version 2.0





Print Date 04.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD 905 ALL WEATHER ROOF COATING

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company

Site 41

Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - repeated exposure, Category 1, Central nervous

system

H372: Causes damage to organs through pro-

longed or repeated exposure.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING





Revision Date 04.08.2017 Version 2.0

Print Date 04.08.2017

Hazard statements H226 Flammable liquid and vapour.

May be fatal if swallowed and enters air-H304

ways.

Causes damage to organs (Central nervous H372

system) through prolonged or repeated ex-

posure.

Prevention: Precautionary statements

> P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ va-

pours/ spray.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immedi-P303 + P361 + P353

ately all contaminated clothing. Rinse skin

with water.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

265-191-7 solvent naphtha (petroleum), medium aliph.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	Classification	Concentration
CAS-No.	(REGULATION (EC)	[%]
EC-No.	No 1272/2008)	
Registration number		
solvent naphtha (petroleum), medium aliph.	Flam. Liq.3; H226	>= 25 - < 40
64742-88-7	STOT RE1; H372	
265-191-7	Asp. Tox.1; H304	
01-2119537181-47-XXXX		
Substances with a workplace exposure limit :		
Asphalt		>= 60 - < 80
8052-42-4		
232-490-9		

For the full text of the H-Statements mentioned in this Section, see Section 16.

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING







Print Date 04.08.2017

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Risk of serious damage to the lungs (by aspiration).

May be fatal if swallowed and enters airways.

Causes damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

Unsuitable extinguishing

media

: Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

: Do not use a solid water stream as it may scatter and spread

fighting

fire.

Country GB 100000008568

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING

Revision Date 04.08.2017 Version 2.0





Print Date 04.08.2017

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible ab-Methods for cleaning up

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when


handling chemical products

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING







fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take pre-

BUILDING TRUST

cautionary measures against electrostatic discharges.

: Handle in accordance with good industrial hygiene and safety Hygiene measures

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

: No data available Specific use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
Asphalt	8052-42-4	TWA	5 mg/m3	GB EH40
		STEL	10 mg/m3	GB EH40

8.2 Exposure controls

Personal protective equipment

Safety glasses with side-shields conforming to EN166 Eye protection

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),

Revision Date 04.08.2017

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING





Version 2.0

Print Date 04.08.2017

breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : black

Odour : characteristic

Odour Threshold : No data available

Flash point : ca. 23 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING







Print Date 04.08.2017

Oxidizing properties : No data available

pH : No data available

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : 0,01 hPa

Density : ca.1,2 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING

Revision Date 04.08.2017 Version 2.0





Print Date 04.08.2017

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or

Country GB 100000008568

8 / 12

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING





Revision Date 04.08.2017

Version 2.0

Print Date 04.08.2017

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1263 **14.2 UN proper shipping name** : PAINT **14.3 Transport hazard** : 3

class(es)

14.4 Packing group: IIIClassification Code: F1Labels: 3Tunnel restriction code: (D/E)14.5 Environmental hazards: no

IATA


14.1 UN number : 1263 **14.2 UN proper shipping name** : Paint **14.3 Transport hazard** : 3

class(es)

14.4 Packing group : III

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING







Print Date 04.08.2017

Labels : 3 14.5 Environmental hazards : no

IMDG

14.1 UN number 1263 14.2 UN proper shipping name PAINT **14.3 Class** 3 14.4 Packing group - 111 Labels 3 EmS Number 1 F-E EmS Number 2 S-E 14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

: Not applicable

(=> 0.1 %).

: Not applicable

: None of the components are listed

- preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1

Quantity 2

FLAMMABLE LIQUIDS P₅c

5.000 t

50.000 t

VOC-CH (VOCV) : 30 %

VOC-EU (solvent) : 30 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING









Print Date 04.08.2017

Health, safety and environmental regulation/legislation specific for the substance or mixture:

Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H372 Causes damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Aspiration hazard Asp. Tox. Flam. Liq. Flammable liquids

STOT RE Specific target organ toxicity - repeated exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route Chemical Abstracts Service

CAS DNFL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

Median lethal concentration (concentrations of the chemical in air that LC50

kills 50% of the test animals during the observation period)

International Convention for the Prevention of Pollution from Ships, MARPOL

1973 as modified by the Protocol of 1978

OFL Occupational Exposure Limit

Persistent, bioaccumulative and toxic **PBT PNFC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament and of the **REACH**

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

Substances of Very High Concern **SVHC** Very persistent and very bioaccumulative vPvB

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

according to Regulation (EC) No. 1907/2006

EVERBUILD 905 ALL WEATHER ROOF COATING









Print Date 04.08.2017

Changes as compared to previous version!