

## PRODUCT DATA SHEET

# EVERBUILD® EVERFLEX® 115 GP Building Mastic

### A TRADITIONAL OIL-BASED POINTING MASTIC

#### PRODUCT DESCRIPTION

EVERBUILD® EVERFLEX® 115 GP Building Mastic is an oil-based compound intended for general pointing and sealing of many joints in traditional forms of construction. EVERBUILD® EVERFLEX® 115 GP Building Mastic provides an effective weatherproof seal.

#### USES

- Perimeter pointing internally and externally around doors and windows.
- Adheres to concrete, brick, wood, metals and glass without the use of a primer.
- Typically used to seal composite sectional panels and low movement vertical building joints.

#### CHARACTERISTICS / ADVANTAGES

- Overpaintable.
- Adheres to most common surfaces.
- Semi drying - remains permanently plastic beneath surface skin.
- High solids formulation - excellent gap filling properties.
- Good external weathering properties.

<b>Flash Point</b>	65°C
<b>Slump</b>	No slump at 70°C when placed in an 18 x 10mm aluminium channel positioned vertically
<b>UV Resistance</b>	Mechanical properties will not change, however product may discolour. Overpainting is recommended
<b>Overpaintability</b>	Use conventional decorative paints to increase durability if required.

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Thixotropic paste (ready to use)
<b>Packaging</b>	285ml Cartridge
<b>Colour</b>	Brown, Grey, Stone, White
<b>Shelf Life</b>	18 months from date of manufacture when stored in original unopened containers.
<b>Storage Conditions</b>	Store in original unopened containers between 15°C and 20°C
<b>Density</b>	1.6 g/cm <sup>3</sup> approx

## TECHNICAL INFORMATION

<b>Movement Capability</b>	Low
<b>Service Temperature</b>	-25°C to 70°C (90°C intermittent)
<b>Joint Design</b>	<b>Minimum width:</b> 5mm. <b>Maximum width:</b> 20mm. <b>Minimum depth:</b> 10mm. <b>Maximum depth:</b> 20mm. For deep joints, reduce depth by using EVERFLEX® FIX AND FILL FOAM or a suitable joint backer rod. All joints should be designed so that the seal is placed in a position which does not retain water or form a water trap. Triangular fillets should be no less than 12mm across the face and should be finished with a flat or convex face.

## SYSTEM INFORMATION

<b>Compatibility</b>	Can be used in contact with most building materials but should not be used against bituminous compounds.
----------------------	--

## APPLICATION INFORMATION

<b>Consumption / Yield / Dosage (PRINT single line)</b>	Approx 10 linear metres per cartridge
<b>Ambient Air Temperature</b>	5°C to 50°C
<b>Curing Time</b>	Normally 7 days, the mass below remaining plastic

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The surfaces to be must be clean, dry and free from dust, grease and other contaminants. New concrete or mortar should be allowed adequate time to dry and mature.

### APPLICATION METHOD / TOOLS

Cut the tip off the cartridge taking care not to damage the thread. Apply nozzle and cut at an angle of 45° with an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the trigger and keeping the gun at a constant angle to the surface being sealed. To ensure a proper bond, always smooth the sealant down with a spatula or piece of wood wetted with linseed oil or white spirit. An improved joint appearance can be achieved by placing masking tape to both sides of the joint, removing within 5 minutes of application.

### CLEANING OF TOOLS

Cleaner: white spirit.

### LIMITATIONS

- Do not use in areas likely to be exposed to solvents, petrols or oils.
- Do not apply to fresh concrete or mortar. Allow 28 days to reduce surface alkalinity.
- Do not use in conjunction with bitumen or asphalt, Use WEATHER MATE®.
- May stain marble, slate or certain sensitive natural stones.

- Do not use on uPVC, polycarbonate or acrylic sheet. Use SILICONE 450.
- Do not use in areas where movement exceeds +/- 5%.
- The product takes 24 –48 hours to skin. It should not be used therefore in areas where it is likely to be subjected to interference or damage (eg floor joints). In such cases, use PURAFLEX 40.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a

particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

**SIKA LIMITED**

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

**SIKA IRELAND LIMITED**

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

**Product Data Sheet**

EVERBUILD® EVERFLEX® 115 GP Building Mastic  
June 2018, Version 01.01  
020511080000000024

**BUILDING TRUST**

EVERBUILD EVERFLEX 115 GP Building Mastic-en-GBEVER-(06-2018)-1-1.pdf