

PRODUCT DATA SHEET

EVERBUILD® EVERFLEX® 145 Butyl Rubber Sealant

SEMI-SETTING BUTYL RUBBER SEALANT

PRODUCT DESCRIPTION

EVERBUILD® EVERFLEX® 145 Butyl Rubber Sealant is a traditional permanently plastic one component sealant based on Polybutene that provides an effective weatherproof seal in a variety of exterior and interior applications. EVERBUILD® EVERFLEX® 145 Butyl Rubber Sealant forms a skin in approximately 24hrs but remains permanently plastic underneath. The sealant accommodates joint movement of +/- 5% and is over paintable.

USES

- Single glazing of metal, concrete and wooden frames.
- Sealing metal roof panels.
- Pointing around soft and hardwood timber, metal and concrete/stone window and door frames.
- Sealing pre-cast concrete panels.
- Sealing timber sections to brick, stone and concrete; ideal for roofline applications.
- Sealing gaps and cracks in brickwork and stone.

CHARACTERISTICS / ADVANTAGES

- Overpaintable.
- Adheres to most common building surfaces.
- Semi drying – forms a surface skin but remains permanently plastic beneath.
- High solids formulation - excellent gap filling properties without shrinkage.
- Good external weathering properties.

Overpaintability

Most decorative paints.
Compatibility test is always recommended.

Cleaner

White spirits.

PRODUCT INFORMATION

Chemical Base	Thixotropic paste (ready to use).
Packaging	300ml cartridge.
Colour	Grey
Shelf Life	24 months from date of manufacture when stored in original unopened containers.
Storage Conditions	Store in original unopened containers between 15 and 20°C.
Density	1.5-1.6 g/cm ³ approx.
Movement Capability	+/- 5%

APPLICATION INFORMATION

Yield	Approx 11 linear meters per cartridge using a 6mm bead.
Substrate Temperature	5°C to 35°C
Curing Time	Skins within 24hrs remains plastic underneath.

SUBSTRATE PREPARATION

All surfaces to be sealed must be sound, dry and clean. The depth of the joint should be approximately 50% of the width. Reduce joint depth with Fix & Fill Expanding Foam or Backer Rod.

APPLICATION METHOD / TOOLS

Cut the tip of the cartridge, taking care not to damage the thread.

Apply nozzle and cut cleanly at an angle of 45 degrees with an opening slightly larger than the gap to be sealed.

Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the gun trigger and keeping the gun at a constant angle to the surface to be sealed.

To ensure a proper bond, always smooth down sealant using a spatula or piece of wood wetted with soap and water solution.

Tool down within 1 hour of application.

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

LIMITATIONS

- Do not use in conjunction with bitumen or asphalt – use WEATHER MATE.
- Do not use on plastic, PVCu windows, polycarbonate or acrylic sheet.
- The sealant will skin in 24-48 hrs but will remain plastic underneath. For this reason, it should not be used in areas where it will be subjected to interference or damage (e.g. floor joints). In these cases, use Puraflex 40 Sealant.
- Do not use in applications where joint movement will exceed +/- 5%.
- It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILD EVERFLEX 145 Butyl Rubber Sealant-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet

EVERBUILD® EVERFLEX® 145 Butyl Rubber Sealant
March 2018, Version 01.01
020511080000000025