

PRODUCT DATA SHEET

EVERBUILD® Filler Coat

A THICK BASECOAT FOR USE ON IMPERFECT SURFACES PRIOR TO PAINTING

PRODUCT DESCRIPTION

EVERBUILD® Filler Coat is a thick basecoat for use on imperfect surfaces prior to painting. It hides areas that have been filled, as well as covering and preventing the reappearance of hairline cracks. Working like a roll-on filler, the thick formula completely covers strong colours and is ideal for use on walls and ceilings.

USES

- Hiding areas that have been filled
- Covering and preventing the reappearance of hairline cracks
- Completely covering strong colours
- Ideal for use on walls and ceilings

CHARACTERISTICS / ADVANTAGES

- Ready to use
- Easily covers imperfect surfaces
- Quick application by roller
- Can be used on ceilings as well as walls

Viscosity	15000-50000 cP
pH	7.5 – 8.9
Application Temp	5°C to 30°C

PRODUCT INFORMATION

Packaging	5L bucket
Appearance / Colour	White
Shelf Life	Use within 24 months.
Storage Conditions	Store in cool dry conditions between +5°C and +25°C. Storage outside these parameters will dramatically reduce shelf life. Protect from frost.
Density	1.4 - 1.5g/cm ³

APPLICATION INFORMATION

Consumption	5-8m ² per litre depending on porosity of surface
Drying time	4-6 hours at 20°C 50% R.H.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Before applying, ensure surfaces are clean, sound and free from dust, crumbly material or any contaminants. Fill any surface defects with Everbuild® Fill & Skim and smooth down. Glossy surfaces must be sanded and then cleaned with Everbuild® Sugar Soap Liquid. Cover furniture and floors etc with protective sheeting such as Everbuild® Dust Sheets or Roll & Stroll Floor Protectors, and open windows /doors to assist in ventilation. New plaster and very porous or powdery surfaces should be primed first with EVERBUILD® Filler Coat diluted 1 part EVERBUILD® Filler Coat to 4 parts water and allowed to dry.

APPLICATION

Stir EVERBUILD® Filler Coat well before use. Touch in corners with a brush and apply an even coat with a short-pile roller or suitable brush – do not overspread. Leave to dry for approximately 4 -6 hours minimum (longer in cold temperatures) before overcoating with emulsion based paint.

NOTE: Ensure EVERBUILD® Filler Coat has completely dried before overpainting. On very bold colours, a second coat may be required.

LIMITATIONS

- Do not apply in temperatures below 10°C
- Do not apply to heated surfaces.
- This product will fill minor surface imperfections. For holes, use a suitable filler from the Everbuild range of products.
- Very porous and powdery surfaces must be primed prior to painting.
- New plaster must be primed and fully dry before applying filler coat.
- Do not use in contact with bitumen.
- As the manufacturer cannot be aware of all the uses their products may be used for, it is the user's responsibility to determine suitability for use. If in doubt contact technical services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILD Filler Coat-en-GBEVER-(05-2018)-1-1.pdf