

PRODUCT DATA SHEET

EVERBUILD FOREVER WHITE® Grout Reviver

FOR RESTORING DISCOLOURED AND DIRTY GROUT TO A BRIGHT WHITE FINISH

PRODUCT DESCRIPTION

EVERBUILD FOREVER WHITE® Grout Reviver is the easy way to revive and restore discoloured and dirty grout to a bright white finish.

With Mould Shield® the leading anti-bacterial solution integrated into the manufacturing process, EVERBUILD FOREVER WHITE® Grout Reviver is proven to stop mould, mildew and bacterial growth. Mould Shield®, in conjunction with Everbuild deliver high quality antimicrobial products, manufactured in the UK and rigorously tested in accredited microbiological laboratories to show no mould growth after 10 years simulated ageing and actively prevent the growth of bacteria, mildew and black mould that are commonly found in areas of high humidity.

Copies of test data are available upon request.

Forever White Grout Reviver dries to an extra brilliant white finish.

USES

- Kitchen/Bathroom walls.
- Shower areas.
- Wet rooms.

CHARACTERISTICS / ADVANTAGES

- Excellent water resistance.
- Dries brilliant white.
- Contains Mould Shield® - prevents mould growth.
- Ready mixed formula - no mixing, no mess.
- Apply straight from the tube with the easy to use applicator.

PRODUCT INFORMATION

Packaging	200ml Squeezy Tube
Colour	White
Shelf Life	Minimum 12 months when stored according to manufacturer's instructions.
Storage Conditions	Store at 5 - 25°C. PROTECT FROM FROST.
Density	1.46 g/cm ³

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Surfaces must be clean, dry and dust free. Remove any old mould with Everbuild 404 Fungicidal Wash prior to application and allow to dry. Replace any damaged, loose or cracked grouting by raking and re-grouting with Everbuild Tile Adhesive; then allowing to dry. Certain tiles (e.g. non glazed; metallic; textured or hand painted) may not be compatible with this product. Always test a small inconspicuous area for compatibility prior to full scale application.

APPLICATION

Remove cap and squeeze the EVERBUILD FOREVER WHITE® Grout Reviver tube until product is expelled. Continue squeezing and apply to grout lines in a zig zag motion ensuring even coverage and working well into existing grout. Allow to dry for 3-4 hours then remove any excess product from tiles with a damp cloth or sponge. Any residue still remaining on tiles can easily be removed by moistening; leaving for 15 minutes then removing as above.

A second application may be necessary for badly stained areas; after first coat is dry (3-4hours). After removal of residues; polish tiles with a clean dry cloth. Avoid wetting tiles for 24 hours after application (longer in cold poorly ventilated/humid conditions). Rinse applicator sponge in warm water after use and replace cap to enable product to be used again. Wash hands with warm water and soap after use.

LIMITATIONS

- Allow to fully dry before exposure to water.
- Do not use over epoxy grout.
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services department for advice or refer to Technical Data Sheet. In all circumstances, the manufacturer's liability is limited to the value of the manufacturer's product purchased

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland