

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : F/WHITE POW WALL TILE GROUT NEW BAG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Grouting mortar

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
Prevention:
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

- Cement (chromium reduced)
- 2-octyl-2H-isothiazole-3-one (OIT)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
---------------	--	----------------	--------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



Cement (chromium reduced)	65997-15-1 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 25 - < 50
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1 247-761-7	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,05 - < 0,25
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 2,5 - < 5

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



Risks : Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
: irritant effects
sensitising effects
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
- Further information on storage stability : Keep in a dry place. No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Cement (chromium reduced)	65997-15-1	TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable,			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



	thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



	particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Recommended: Butyl rubber/nitrile rubber gloves.
Contaminated gloves should be removed.
- Skin and body protection : Dust impervious protective suit
Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



exposure levels, the hazards of the product and the safe working limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: powder
Colour	: white
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1,2 g/cm ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0



BUILDING TRUST



Print Date 15.11.2019

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Country GB 100000007247

10 / 14

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



specific for the substance or mixture:

Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

F/WHITE POW WALL TILE GROUT NEW BAG

Revision Date 15.11.2019

Version 5.0

Print Date 15.11.2019



BUILDING TRUST



	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN