

PRODUCT DATA SHEET

EVERBUILD® JETCEM® PATCHING PLASTER

A HIGH STRENGTH PATCHING PLASTER

PRODUCT DESCRIPTION

EVERBUILD® JETCEM® PATCHING PLASTER is a high strength plaster in powder form which mixes easily with water to form a creamy lump free paste that is the ideal choice for most patching repairs. The product dries hard in 1 hour to a smooth finish which can be further sanded if desired. With added PVA powder, this product will not shrink or crack and is strong enough to accept nails or screws.

USES

- Plaster
- Plasterboard
- Brick
- Wood
- Stone
- Most other building materials

CHARACTERISTICS / ADVANTAGES

- Dries in 1 hour.
- Easy mixing, just add water.
- Adheres to most common building surfaces.
- Overpaintable.
- Doesn't shrink or crack.

PRODUCT INFORMATION

Packaging	6kg Bag
Appearance / Colour	White
Shelf Life	24 months in original unopened bag. This will reduce significantly once opened.
Storage Conditions	Store in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.
Density	ca. 1.2 g/cm ³

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Before applying, ensure surfaces are clean and free from dust, crumbly material or any contaminants, which may affect adhesion. Cover nail or screw heads with oil based paints and allow to dry. Dampen all porous surfaces to improve adhesion.

APPLICATION

- Always use a clean mixing vessel and add approx. 2 ½ parts powder to one part by volume clean cold water and mix immediately to a smooth paste. The mixed plaster will remain workable for 30-40 minutes.
- Smooth the EVERBUILD® JETCEM® PATCHING PLASTER over the repair with a trowel.
- Finish with a wet knife, if sanding is desired fill the hole slightly proud to allow for sanding down.

FINISHING

- EVERBUILD® JETCEM® PATCHING PLASTER is normally sandable and overpaintable after approximately one hour.
- Once dry, sand to a smooth finish.
- EVERBUILD® JETCEM® PATCHING PLASTER may be painted or papered when dry.

LIMITATIONS

- For holes deeper than 4cm / 1 ½ inch, apply in layers and allow to dry before applying second layer.
- Do not add further water once the plaster has started to go off. Remix a fresh batch.
- Allow to fully dry before over coating.
- Only use on porous surfaces. Do not apply over plastics, sealants or paints.
- Wood repairs – do not use in areas where impact resistance or flexibility is required, e.g. door surrounds. Use EVERBUILD HIGH PERFORMANCE WOOD FILLER.
- Do not use below 10°C.
- It is always the user's responsibility to determine suitability of use. If in doubt, request technical data or contact technical services.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDJETCEMPATCHINGPLASTER-en-GBEVER-(04-2018)-1-1.pdf