

## PRODUCT DATA SHEET

# EVERBUILD® Lead Mate® Patination Oil

### A PROTECTIVE COATING ON ALL NEWLY FIXED LEADWORK

#### PRODUCT DESCRIPTION

EVERBUILD® Lead Mate® Patination Oil has been specially formulated to provide a protective coating for newly installed leadwork that helps to prevent the white carbonate staining that affects new lead and surrounding tiles, brickwork, stonework etc.

Just one coat of EVERBUILD® Lead Mate® Patination Oil also helps to provide uniform, attractive appearance to newly installed lead and helps the ageing process whilst the natural patina of the lead is being formed.

It is particularly important to treat areas of newly installed lead that are subject to water flowing over the surface onto surrounding areas as staining of tile and brick will be more severe in such circumstances.

#### USES

- Areas of newly installed lead that are subject to water flowing over the surface onto surrounding areas.
- Newly fixed lead work.

#### CHARACTERISTICS / ADVANTAGES

- Works on all newly fixed lead work.
- Prevent unsightly staining.
- Improves initial appearance and assists in natural ageing of lead.
- No spill pack for clean and easy application.

<b>Boiling Point</b>	152°C
<b>Working Temperature</b>	5 - 35°C (keep below flash point)
<b>Coverage</b>	Approximately 55-65 m <sup>2</sup> / L

#### PRODUCT INFORMATION

<b>Packaging</b>	500ml and 1L Self-gaging plastic bottle
<b>Appearance / Colour</b>	Brown / Yellow liquid
<b>Shelf Life</b>	12 months from date of manufacture when stored as directed
<b>Storage Conditions</b>	Store in cool, dry conditions between +5 and +30°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life.
<b>Density</b>	~0.8 g/cm <sup>3</sup>
<b>Flash Point</b>	38°C

#### APPLICATION INSTRUCTIONS

##### SUBSTRATE PREPARATION

Always wear gloves and only apply in a well ventilated area. Shake can well before use.  
Surfaces must be totally dry before application.

##### APPLICATION METHOD / TOOLS

Apply oil evenly using a soft absorbent cloth, work horizontally starting at the top and maintain a wet edge at all times.

DO NOT APPLY IN A CIRCULAR MOTION AS THIS WILL LEAVE AN IMPRESSION ON THE LEAD.

Only one coat is required. Before clipping apply to underside of lead to approx 50mm from the edge. Apply to all areas, including clips and trim, and coat between

laps.

**VERY IMPORTANT** – Always apply as soon as possible after installation, or at the end of each working day, or if rain is expected apply before rain.

## LIMITATIONS

- Do not allow EVERBUILD® Lead Mate® Patination Oil to come into contact with Bitumen or Polycarbonate sheets.
- Always test a small inconspicuous area prior to full application.
- As the company cannot be aware of all the applications and materials its product may be used on, it is the user's responsibility to determine suitability for use. Please contact Technical Services for advice.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland