

# PRODUCT DATA SHEET

# EVERBUILD® Multi-Purpose Wood Filler

## PREMIUM JOINERS GRADE WOOD FILLER

### PRODUCT DESCRIPTION

EVERBUILD® Multi-Purpose Wood Filler is an easy to use ready mixed premium joiners grade filler ideal for filling small imperfections (max 5mm depth) in wood. Once dry, the filler leaves a sandable surface, which can be stained, painted or varnished even with micro-porous stains. The filler is waterproof when dry and hence is suitable for exterior as well as interior applications.

### USES

- Filling small holes, splits, surface imperfections and damaged areas in wood.
- Covering the recesses left by nails and screws.

### CHARACTERISTICS / ADVANTAGES

- Water based filler
- Non flammable
- Low odour
- Ready to use – no mixing of components required.

<b>Base</b>	Styrene Acrylic copolymer
<b>Consistency</b>	Stable paste

### PRODUCT INFORMATION

<b>Packaging</b>	100ml & 250ml tubs
<b>Appearance / Colour</b>	Dark Oak, Light Oak, Mahogany, Pine, Teak ,White, Light Stainable, Medium Stainable
<b>Shelf Life</b>	24 months in original containers at stated storage temperatures.
<b>Storage Conditions</b>	Store in cool dry conditions, away from direct sunlight between 5 and 25°C. PROTECT FROM FROST.
<b>Density</b>	1.73 - 1.83 g/cm <sup>3</sup>
<b>Ambient Air Temperature</b>	Application Temps +5°C to +40°C. (Optimum 20°C). Temperature Resistance -5°C to +70°C.
<b>Applied Product Ready for Use</b>	Touch Dry 15 minutes @ 20°C Through Hard 2 hours @ 20°C Sandable 30 minutes @ 20°C Overpaintable 2 Hours @ 20°C

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

NOTE: If you intend to overstain the wood (once filled) ALWAYS CHOOSE THE COLOUR OF FILLER THAT NEAREST MATCHES THE WOOD YOU ARE FILLING, NOT THE STAIN YOU INTEND TO USE.

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants which may affect adhesion

### APPLICATION

Stir well before use and apply with a spreader or knife. Fill the hole proud to allow for sanding. Once dry, sand to a smooth finish and apply required stain.

### LIMITATIONS

- As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first. Note: filler may dry darker.
- Do not exceed 5mm in one coat. For holes deeper than 5mm or for areas subject to impact such as doors and window frames, use EVERBUILD 2 PART HIGH PERFORMANCE WOOD FILLER which can be applied to any depth and is shatterproof.
- When used externally protect from rain for at least 5 hours.
- Do not apply below 5°C.
- As the manufacturer cannot know all the uses their products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice.

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

#### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

#### SIKA IRELAND LIMITED

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

EVERBUILDMulti-PurposeWoodFiller-en-GBEVER-(04-2018)-1-1.pdf