

PRODUCT DATA SHEET

EVERBUILD® PINKGRIP DRYFIX® FR

A revolutionary fast cure wall adhesive foam

PRODUCT DESCRIPTION

EVERBUILD® PINKGRIP DRYFIX® FR DUAL FLOW is a revolutionary new type of fast curing adhesive foam that has been specially developed for the rapid installation of Plasterboard, Insulation Boards and other materials such as Roof Decking and Floorboards. Conforms to EN 13501 (Fire classification of construction products and building elements Part 1: Classification using data from reaction to fire tests) Class E.

Supplied in a pressurised canister EVERBUILD® PINKGRIP DRYFIX®

FR DUAL FLOW is applied with either an applicator gun or standard applicator nozzle.

Note: PINKGRIP DRYFIX® must only be applied using the PINKGRIP DRYFIX® Applicator Gun, ordinary Foam Guns must not be used.

USES

- For fixing Plasterboard to solid walls.
- For fixing Plasterboard to metal and timber stud walls and battens.
- Bonding insulation boards to most substrates.
- Fixing Roof Decking and Floorboards to beams.
- Bonds to: Masonry, Concrete, Plaster, Timber, Metal, Insulation boards, Polystyrene, Polyurethane, Bitumen, Asphalt and much more.

PRODUCT INFORMATION

Chemical Base	Polyurethane
Packaging	750 ml
Colour	Pink
Shelf Life	12 months from date of manufacturer (see base of can for expiry date) when stored in original unopened cans between +15 and +20 °C in vertical position – always keep can upright. Once opened, shelf life is reduced to one month from original use.
Storage Conditions	Store can upright between +15 and +20 °C.

CHARACTERISTICS / ADVANTAGES

PINKGRIP DRYFIX® FR provides significant time, labour and convenience benefits when compared to traditional dry wall adhesives, summarised as follows:

QUICK

- 30 % time saving over conventional dry wall adhesives.
- Board only needs holding for 1 minute.
- Can be plastered in ONE HOUR.
- Canister can be left on gun for immediate re-use.

CLEAN

- No mixing.
- No mess.
- No water.
- No bucket.
- No dust.

CLEVER

- No heavy bags to carry.
- One canister fixes up to 5 standard boards.
- Can be applied to board or wall.
- Works on solid walls, metal & timber studding.
- Timed delay prevents post expansion once in position.
- Helps to reduce cold bridging.
- No nails or screws. No filling over or popping out.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

IMPORTANT – Clean the gun immediately after use with EVERBUILD® DUAL PURPOSE FOAM CLEANER. Re-use is only possible by leaving the gun attached to this can and cleaning foam from the gun nozzle tip with EVERBUILD® DUAL PURPOSE FOAM CLEANER before the foam has cured.

Re-use must be within 1 month of original use.

NEVER STORE THIS CAN HORIZONTALLY. The valve may seize and fail to activate.

NEVER PUSH ANY OBJECT INTO VALVE AS CONTENTS MAY EXPLODE. If any can fails to activate, do not interfere with valve. Return can to your supplier.

ALWAYS USE FOAM CANS AT A TEMPERATURE OF +2 to +20 °C or foam will not discharge correctly. This may be achieved by warming can gently in a bucket of warm water.

Cured foam residues may be removed mechanically. Dispose of this material and its container to hazardous or special waste collection point.

ECOLOGY, HEALTH AND SAFETY

APPLICATION INSTRUCTIONS

PINKGRIP DRYFIX® FR is a revolutionary new adhesive and like most building products there's a knack to using it. Here's a few tips on getting the best out of it:-

SUBSTRATE PREPARATION

- Shake can well, about 20 times before using (and occasionally during use).
- Surfaces must be clean, sound and dust free, ensure metals are free from any grease or oils.
- Only apply in temperature range +2 °C to +25 °C.
- Turn can upside down and screw gun carefully onto the black adaptor of the can.
- Must only be applied using a PINKGRIP DRYFIX® Applicator Gun or supplied nozzle. Ordinary Foam Guns **MUST NOT BE USED.**
- If can has been kept in cold conditions bring to room temperature before use: a handy way is to stand the can in a bucket of hot water. Do not heat up by any other method.

CLEANING OF TOOLS

Excess adhesive or spillages can be removed whilst still wet with Everbuild® Dual Purpose Foam Cleaner. Use Dual Purpose Foam Cleaner to keep the nib of the gun clean during use, and before storage. To clean the applicator nozzle, remove from the can and spray with Everbuild Dual Purpose Foam Cleaner. Always ensure the valve is cleaned thoroughly. Everbuild Wonder Wipes will remove wet and semi-cured foam from hands and most surfaces.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
EVERBUILD® PINKGRIP DRYFIX® FR
February 2023, Version 02.01
020514060000000092

EVERBUILD PINKGRIP DRYFIX FR-en-GB-(02-2023)-2-1.pdf