

## PRODUCT DATA SHEET

# EVERBUILD® Quick Drying Clear Varnish

ENHANCES THE NATURAL QUALITIES OF WOOD AND PROVIDES LONG LASTING PROTECTION

## PRODUCT DESCRIPTION

EVERBUILD® Quick Drying Clear Varnish is a professional, low solvent varnish that enhances the natural qualities of wood, and provides long lasting protection. It has been developed specifically to give an ultra-hard, scratch resistant and heat resistant, non-yellowing finish.

## USES

Ideal for use on interior wood such as:

- Tables
- Chairs
- Doors
- Skirtings
- Furniture etc.

## CHARACTERISTICS / ADVANTAGES

- Low solvent formula
- Touch dry in 30 minutes, overcoat after 1 hour
- Long lasting protection
- Clear finish, no discoloration
- Ultra hard finish
- Scratch resistant
- Heat resistant
- Non-yellowing finish
- Easy to apply

## PRODUCT INFORMATION

<b>Packaging</b>	250ml, 750ml and 2.5ltr tins
<b>Colour</b>	Clear Varnish in Gloss, Matt and Satin finishes
<b>Shelf Life</b>	24 months from date of manufacture when stored as directed.
<b>Storage Conditions</b>	Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. Protect from frost.
<b>Density</b>	1.0 - 1.1 g/cm <sup>3</sup>
<b>pH-Value</b>	7.5 - 9
<b>Volatile organic compound (VOC) content</b>	Volatile Organic Compounds contribute to atmospheric pollution. EU limit value for this product (cat A/e): 130g/L (2010). This product contains max 60g/L VOC.

## APPLICATION INFORMATION

<b>Consumption</b>	Up to 16m <sup>2</sup> /litre depending on porosity of wood and number of coats applied
<b>Ambient Air Temperature</b>	Do not use in temperatures below 10°C.

## APPLICATION INSTRUCTIONS

### MIXING

Stir product well before use and intermittently during application.

### SUBSTRATE PREPARATION

Ensure wood is clean, dry and free from dirt or dust by wiping with a lint free cloth dampened with white spirit, allow to dry before applying EVERBUILD® Quick Drying Clear Varnish.

On varnished wood, remove any unsound varnish and sand the surface with medium grade sandpaper to a uniformed appearance and then clean with white spirit. Allow to dry thoroughly before applying EVERBUILD® Quick Drying Clear Varnish. On bare wood, sand the surface with fine sandpaper. Always remove excess dust with a cloth before applying varnish.

### APPLICATION

Brush apply EVERBUILD® Quick Drying Clear Varnish, following the direction of the wood grain. Always apply the varnish to a wet edge, working systematically across the surface keeping the wet edge moving together as much as possible. The film is touch dry in 30 minutes. Approximately 2-3 coats will be required for full coverage. Allow 1 hour between each coat. Lightly sand the surface before applying the final coat.

Note: on application, the varnish will appear slightly white; this quickly turns completely clear as the drying process starts.

### CLEANING OF TOOLS

Clean brushes thoroughly with water after use; a little washing up liquid will assist brush cleaning.

## MAINTENANCE

### CLEANING

If water is accidentally spilt on the surface within 2-3 days of application, remove by wiping gently (do not rub) with a soft cloth.

## LIMITATIONS

- Do not use on wood floors or decking.
- Do not use externally.
- Protect from frost and do not use in temps below 10°C.
- To avoid risk of spillage, always transport this tin in a secure and upright position.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

**SIKA LIMITED**

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

**SIKA IRELAND LIMITED**

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

EVERBUILDQuickDryingClearVarnish-en-GBEVER-(04-2018)-1-1.pdf

Product Data Sheet  
EVERBUILD® Quick Drying Clear Varnish  
April 2018, Version 01.01  
020405030040000015