Profile-Line® Tile Vents














Related products

Adaptor & Flexipipe KG979200 Flexipipe 100/100mm KG979900 Soil/Mechanical Adaptor KG979100

Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.

Product features & benefits

- In-line design makes it unobtrusive on the roof line
- Can be use at high or low levels and for soil ventilation or mechanical extraction when used with a Klober Flexipipe
- Built-in downpipe ensures ventilation path into roof space
- Adaptor and Flexipipe available for soil ventilation or mechanical extraction
- Complies fully with the relevant Building Regulations and British Standards

Area of application

Suitable for:

- For roofs with a pitch over 20°
- Single Pantile Vent: suits Sandtoft Shire Pantile, Redland Norfolk Pantile, Marley Anglia and Forticrete Centurion interlocking tiles
- 15x9 Vent: suits Redland 49, Marley Ludlow Plus, Sandtoft Standard Pattern, and Forticrete V2 interlocking tiles
- Flat Vent: suits Marley Modern, Redland Mini Stonewold, Russell Grampian and Sandtoft Calderdale profiles

Material

UPVC (Flat Vent)

Polypropylene (15 \times 9 & Single Pantile)

Colours / Product Codes

Single Pantile Vent	KG9860
15x9 Vent	KG9690
Flat Vent	KG9856
Antique Red	-0116
Brown	-0247
Slate Grey	-0429
Terracotta	-01.52

Black -0450 (only Flat Vent)

Dimensions

384mm long x 229mm wide (Single Pantile/15x9 Vent) 418mm long x 330mm wide (Flat Vent)

Packaging

10 pcs per carton

Weight (per carton)

Single Pantile 5.5kg 15 x 9 Vent 5.5kg Flat Vent 9.0kg

PERFORMANCE / TECHNICAL DATA

Provides 10,000mm² effective area			
5mm opening at 2m centres	25mm opening at 0.4m centres	10mm opening at 1m centres	
Airflow resistance	15 litres/sec	30 litres/sec	60 litres/sec
Single Pantile Vent	12 Pascals	48 Pascals	192 Pascals
15x9 Vent	12 Pascals	48 Pascals	192 Pascals
Flat Vent	7 Pascals	29 Pascals	115 Pascals

TS-00#11-UK-0214. We assume no liability for typing errors.

Klober Ltd



