


# Uni-Plain Tile Vent



## Installation

The Uni-Plain Tile Vent is positioned in broken bond format, above the course below and the underlay is marked and cut to accommodate the downpipe. The Tile Vent is then positioned adjacent to the next tile, nailed in place and tiling continued as normal.

## Regulations and certifications

Complies fully with relevant Building Regulations and British Standards.

Uni-Plain Tile Vent is a discreet ventilating tile suitable for clay and concrete plain tiles that provides 6,000 mm<sup>2</sup> effective ventilation area.

## Product features & benefits

- No batten cutting necessary
- In-line design
- Built in downpipe allows direct ventilation to roof space
- Adaptor available for soil ventilation or mechanical extraction
- Prevents the entry of birds and large insects

## Area of application

Suitable for:

- Most concrete and clay plain tiles at a roof pitch at or over 35°
- High or low level roof space ventilation

## Material

Polypropylene/PVC

## Colours / Product Codes

|                |          |
|----------------|----------|
| Antique Red    | KG991803 |
| Autumn         | KG991823 |
| Brown          | KG991836 |
| Brown Gran     | KG991802 |
| Hedgerow Brown | KG991818 |
| Red Gran       | KG991805 |
| Rustic Red     | KG991878 |
| Slate Grey     | KG991830 |
| Terracotta     | KG991834 |

## Dimensions / Weight (per carton)

300mm long x 330mm wide / 8.5kg

## Packaging

10 pcs per carton

## Related products

|                          |          |
|--------------------------|----------|
| Adaptor & Flexipipe      | KG992800 |
| Adaptor only             | KG990500 |
| Flexipipe only 100/100mm | KG979900 |

## PERFORMANCE / TECHNICAL DATA

Provides 6,000 mm<sup>2</sup> effective vent area

Vent spacing

5mm opening at 1.2m centres  
10mm opening at 0.6m centres  
25mm opening at 0.24m centres

Airflow resistance

|               |               |               |
|---------------|---------------|---------------|
| 15 litres/sec | 30 litres/sec | 60 litres/sec |
| 12 Pascals    | 48 Pascals    | 191 Pascals   |

TS-00#13-UK-0214. We assume no liability for typing errors.

### Klober Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA  
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klober.co.uk · [www.klober.co.uk](http://www.klober.co.uk)

# KLOBER