




The universal solution for ventilating roof voids, compatible with most concrete interlocking roof tiles.

Klober's Universal Tile Vent suits most popular interlocking roof tiles and can be used to ventilate roof voids or as a terminal for soil and ventilation pipes and mechanical extraction systems.



Universal Vent
Adaptor 100mm



Features and benefits

- Design allows direct ventilation to the roof space.
- Can be used as a terminal for soil and ventilation pipes and mechanical extraction systems when used with an adaptor and flexipipe.
- Compatible with 100mm and 125mm adaptors.

Area of application

- For roof pitches 17.5° and over.
- Suits most concrete interlocking and plain tiles.
- High and low level ventilation.

Related products

- Adaptor and 100mm Flexi Pipe combined KG979800-1.
- Universal Vent Adaptor 100mm KG968300-1.
- Universal Vent Adaptor 125mm KG979000-1.
- Flexipipe 100/100mm KG979900.
- Flexipipe 100/125mm KE8047.
- Pipe Sealing Collar KU8001.
- Replacement Cap KG9855.

Approvals and certifications

- Allows ventilation to BS5250.
- All products supplied by Klober Ltd are covered by a 10 year guarantee against manufacturing defect.

Technical guidance

Material	Soft and rigid UPVC.
Minimum Pitch	17.5°
Weight per carton	18.9kg
Ventilation Area	15,000mm ²
Vent tile spacing	5000mm ² /m 3m centres 10,000mm ² /m 1.5m centres 25,000mm ² /m 0.6m centres
Airflow resistance with 100mm adaptor	15 litres/sec 4 pascals 30 litres/sec 16 pascals 60 litres/sec 65 pascals
Airflow resistance with 125mm adaptor	15 litres/sec 3 pascals 30 litres/sec 12 pascals 60 litres/sec 47 pascals
More information	Compatible with plain tiles however battens will need to be cut. Please refer to the installation guide for further guidance.

Product information

Universal Tile Vents						
Product code	Width mm	Length mm	Vent area mm ²	Colour	Box quantity	Pallet quantity
KG985403	424	454	15,000	Antique Red	10	80
KG985430				Slate Grey		
KG985434				Terracotta		
KG985436				Brown		
KG985476				Black		

Klober is certified to ISO 9001:2015 for Quality Management and ISO 14001:2015 for Environmental Management. All Klober products comply fully with all relevant Building Regulations and British Standards.