

Technical Data Sheet

Product

OB41 Electrical Contact Cleaner is a highly efficient general purpose cleaning solvent ideal for the removal of stains, coatings, printing ink, oil, grease and dirt from electrical contacts.

OB41 Electrical Contact Cleaner is a non chlorinated, low toxicity, non corrosive degreaser which leaves no residue and is safe to use on most plastics or fibres. It is suitable for cleaning most electrical apparatus, installations and delicate instruments.

Applications

Electrical Contact Cleaner is suitable for cleaning most electrical components, especially automotive applications.

Electrical Contact Cleaner effectively removes stains, coatings, oil, grease, dirt and other contaminants.

Method of Use

Gently wipe or brush away any surplus grime, oils or other contaminants. Spray generously from distance of about 10-25cm. Repeat if necessary

Handling and Storage Considerations

Whilst handling the product, we advise to avoid spillage, to keep away from heat, sparks and open flames and to use the in well ventilated areas. For best results the product should be used at temperatures between 15°C - 25°C.

OB41 Electrical Contact Cleaner needs to be stored in temperatures between 10°C - 20°C, in dry, well ventilated areas and must not be exposed to direct sunlight or temperatures above 50°C.

Disposal Considerations

The aerosol must be disposed of safely, in accordance with local authority requirements. The empty containers must not be burned because of explosion hazard.

Recommendations

We recommend that you view the Safety Data Sheet (SDS) for further information on the product before use and if you have any questions or queries then you can contact technical services.

Shelf Life

24 months from date of manufacture.

This technical data sheet supersedes all previous issues and users are cautioned to ensure that it is current.

Destroy all previous data sheets and if in doubt contact Siroflex Ltd .

This data was compiled using current safety information supplied by the distributor of raw materials. This product should be used as directed by Siroflex Ltd . For further information consult the product data sheet or contact technical services.