

User Instructions

Product code: OX-S2411 - OX PU Flex Gloves

Description and Sizes: OX PU Flex Gloves – Available Sizes: 8 (M), 9 (L), 10 (XL) & 11 (XXL)

Product Code	Sizes	EN388 Rating
OX-S241108	8/M	3121X
OX-S241109	9/L	3121X
OX-S241110	10/XL	3121X
OX-S241111	11/XXL	3121X

This Glove is a Personal Protective Equipment (PPE) belonging to Category II and it meets the requirements of the PPE Regulation (EU)2016/425 for innocuousness, comfort & Solidity.

EU Type Examination issued by: C.T.C. (0075) 4, rue Hermann Frenkel, 69367 Lyon Cedex 07, France

Applicable Standards:




This glove has been tested in accordance with EN420:2003 + A1:2009 – Protective Gloves – General Requirements and Test Methods
Dexterity: Level 5

EN388:2016 - Protective gloves against mechanical risks



XXXXXX



Performance Level Ratings	1	2	3	4	5
Abrasion Resistance (No. of cycles)	100	500	2000	8000	-
Circular Blade Cut Resistance (Index)	1.2	2.5	5	10	20
Tear Resistance (N)	10	25	50	75	-
Puncture Resistance (N)	20	60	100	150	-

Performance Level Ratings	A	B	C	D	E	F
Straight Blade Cut (TDM) Resistance (N)	2	5	10	15	22	30
Impact Resistance	PASS or FAIL					

An "X" can be shown in place of any of the first 5 digits underneath the pictogram, where the test was either not carried out, not required or not suitable
"0" indicates that the gloves fails below the minimum performance level for the given hazard.
The letter "P" shall be included at the end if the impact test has been passed.

- P Impact Resistance
- A-F Straight Blade Cut (TDM) Resistance
- 1-4 Puncture Resistance
- 1-4 Tear Resistance
- 1-5 Circular Blade Cut Resistance
- 1-4 Abrasion Resistance

Protection Limits:

This glove does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The protection against risks or hazards which are not mentioned in this document are not warranted. The performance levels mentioned are valid for the palm area only and for new gloves not washed nor regenerated. These performance levels are obtained from tests done in accordance to conditions defined by the applicable standards.

Do not use if there is a risk of entanglement with moving parts of machinery.

Keep away from fire.

Care Instructions:

Both new and used gloves should be thoroughly inspected before use for damage. Performance characteristics of damaged or laundered gloves may vary from those of new gloves.

Store in original packaging in clean dry conditions away from direct sunlight.

Manufacturer Address:

OX Products Group UK Ltd
Unit 2, Riverside
Kangley Bridge Road
London
SE26 5DA
United Kingdom
Tel: 0044 (0)20 8676 9990
Fax: 0044 (0)20 8676 7520
sales.uk@oxtools.com
www.oxtools.com