# SAFETY DATA SHEET

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: RONSEAL DIAMOND HARD FLOOR VARNISH
Product code	: AC001S02F103-01
EC number	: Mixture.
CAS number	: Not applicable.
Chemical formula	: Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against		
Material uses	: Paint or paint related material.	

### 1.3 Details of the supplier of the safety data

sheet
Sherwin-Williams UK Limited
Avenue One Station Lane
Witney
Oxfordshire
United Kingdom OX28 4XR
0A20 4AR
+44(0) 344 7369174
Sherwin-Williams (Ireland) Ltd
Unit 53
Robinhood Industrial Estate
Dublin 22 D22PW99
+353 1 2944009
e-mail address of person : uksds@sherwin.com
responsible for this SDS
1.4 Emergency telephone number
National advisory body/Poison Centre
<i>Telephone number</i> 111 (general public) and 0344 892 111 (Medical professional (NHS) only)
Supplier
<i>Telephone number</i> : +44 (0) 344 736 9174 (8am-6pm Mon-Fri)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Date of issue/Date of revision	: 09, Feb, 2023.	Date of previo

AC001S02F103-01

### **SECTION 2: Hazards identification**

		incution
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
General	:	Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	ts
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
		This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

### **SECTION 3: Composition/information on ingredients**

:

#### 3.2 Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
1,2-Benzisothiazolone	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 02-2119677941-26 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319:	[1]

### **SECTION 3: Composition/information on ingredients**

See Section 16 for the full text of the H statements declared above.	0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show the container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li> <li>The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.

#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

#### RONSEAL DIAMOND HARD FLOOR VARNISH

AC001S02F103-01

#### **SECTION 4: First aid measures**

See toxicological information (Section 11)

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	commended: alcohol-resistant foam, carbon dioxide, po	wders.
Unsuitable extinguishing media	not use water jet.	
5.2 Special hazards arising t	e substance or mixture	
Hazards from the substance or mixture	e will produce dense black smoke. Exposure to decompo use a health hazard.	osition products may
Hazardous combustion products	composition products may include the following material bon dioxide, smoke, oxides of nitrogen.	s: carbon monoxide,
5.3 Advice for firefighters		
Special protective actions for fire-fighters	ol closed containers exposed to fire with water. Do not re ains or watercourses.	elease runoff from fire to
Special protective equipment for fire-fighters	e-fighters should wear positive pressure self-contained b CBA) and full turnout gear.	reathing apparatus

#### **SECTION 6: Accidental release measures**

Due to the organic solvents content of the mixture:

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
		Keep unnecessary and unprotected personnel from entering.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and material for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

#### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	: Due to the organic solvents content of the mixture:
	Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

AC001S02F103-01

### SECTION 7: Handling and storage

	<ul> <li>Keep away from heat, sparks and flame. No sparking tools should be used.</li> <li>Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.</li> <li>Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.</li> <li>Put on appropriate personal protective equipment (see Section 8).</li> <li>Never use pressure to empty. Container is not a pressure vessel.</li> <li>Always keep in containers made from the same material as the original one.</li> <li>Comply with the health and safety at work laws.</li> <li>Information on fire and explosion protection</li> <li>Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.</li> </ul>
7.2 Conditions for safe storage, including any incompatibilities	<ul> <li>Store in accordance with local regulations. Notes on joint storage Keep away from: oxidising agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.</li> </ul>
	Contaminated absorbent material may pose the same hazard as the spilt product. Store above 5°C (42°F) Protect from frost.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

#### SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

No exposure limit value known.

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
	required.

#### **DNELs/DMELs**

AC001S02F103-01

### **SECTION 8: Exposure controls/personal protection**

No DNELs/DMELs available.

#### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2-(2-Butoxyethoxy)-ethanol	Fresh water	1 mg/l	-
	Marine water	0.1 mg/l	-
	Fresh water sediment	4.9 mg/kg	-
	Marine water sediment	0.4 mg/kg	-
	Sewage Treatment	200 mg/l	-
	Plant	Ū	
	Secondary Poisoning	56 mg/kg	-
	Soil	0.4 mg/kg	-
	Fresh water	1 mg/l	-
Ammonium Hydroxide	Fresh water	0.0011 mg/l	-
-	Marine water	0.0011 mg/l	-

#### 8.2 Exposure controls

o.z Exposure controis	
Appropriate engineering controls	: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
	: Users are advised to consider national Occupational Exposure Limits or other equivalent values.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	: Wear suitable gloves tested to EN374.
Gloves	: Short term exposure less than 10 minutes Continuous use Nitrile gloves.
	Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time) .
	There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
	Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personnel should wear protective clothing.
	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

AC001S02F103-01

#### **SECTION 8: Exposure controls/personal protection**

Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

#### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

		• •
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Various
Odour	:	Mild.
Odour threshold	:	Not relevant/applicable due to nature of the product.
рН	:	Not Available (Not Tested). insoluble in water.
<i>Melting point/freezing point Initial boiling point and boiling range</i>		Not relevant/applicable due to nature of the product. 100°C
Flash point	:	Closed cup: >93.3°C
Evaporation rate	:	Slower than Ether Phase
Flammability	:	Not relevant/applicable due to nature of the product.
Lower and upper explosion limit	:	LEL: 0.6% (Trimethylpentanediol Isobutyrate) UEL: 4.2% (Trimethylpentanediol Isobutyrate)
Vapour pressure	:	2.3 kPa (17.5 mm Hg)
Relative vapour density	:	Not relevant/applicable due to nature of the product.
Relative density	:	1.026733236
Solubility(ies)	:	Not relevant/applicable due to nature of the product.
Solubility in water	:	Not relevant/applicable due to nature of the product.
Partition coefficient: n-octanol/ water	:	Not relevant/applicable due to nature of the product.

:

### Auto-ignition temperature

Ingredient name		°C	°F	Method	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol		392	737.6		
Decomposition temperature	: Not	relevant/applic	able due to nature	of the product.	
Viscosity	: Kine	ematic (40°C):	>20.5 mm²/s		
Explosive properties	: Uno	der normal cono	ditions of storage ar	nd use, hazardous reactions will not occur	
Oxidising properties	: Und	der normal cono	ditions of storage ar	nd use, hazardous reactions will not occur	
Particle characteristics					
Median particle size	: Not	relevant/applic	able due to nature	of the product.	

Date of issue/Date of revision : 09, Feb, 2023.

#### **SECTION 9: Physical and chemical properties**

#### 9.2 Other information

Heat of combustion

: 1.259 kJ/g

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).				
10.3 Possibility of hazardous reactions	: No specific test data related to reactivity available for this product or its ingredients.				
	Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.				
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.				
10.6 Hazardous decomposition products	<ul> <li>Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.</li> </ul>				

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-Benzisothiazolone reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral LD50 Oral	Rat Rat	1020 mg/kg 53 mg/kg	-

#### Acute toxicity estimates

No data available

AC001S02F103-01

### **SECTION 11: Toxicological information**

Irritation/Corrosion					
Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzisothiazolone reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Mild irritant Skin - Severe irritant	Human Human	-	48 hours 5 % 0.01 %	-
Conclusion/Summary	: Not available.	·	•		
<u>Sensitisation</u> Conclusion/Summary <u>Mutagenicity</u> No data available	: Not available.				
<u>Carcinogenicity</u> No data available					
<u>Reproductive toxicity</u> No data available					
<u>Teratogenicity</u> No data available					
Specific target organ toxicity No data available	<u>/ (single exposure)</u>				
<u>Specific target organ toxicity</u> No data available	<u>/ (repeated exposure)</u>				
Aspiration hazard No data available					
11.2 Information on other haz					
<b>11.2.1 Endocrine disrupting</b> Not available.	properties				
11.2.2 Other information					
Not available.					

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

C50 10 to 20 mg/l Fresh water	dubia .	48 hours 48 hours 96 hours
(	C50 10 to 20 mg/l Fresh water	C50 10 to 20 mg/l Fresh water Crustaceans - Ceriodaphnia dubia

#### 12.2 Persistence and degradability

Conclusion/Summary : Not available. RONSEAL DIAMOND HARD FLOOR VARNISH AC001S02F103-01

### **SECTION 12: Ecological information**

#### 12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

13.1 Waste treatment metho	S
<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: No.
European waste catalogue (EWC)	: 08 01 12 waste paint and varnish other than those mentioned in 08 01 11
Disposal considerations	<ul> <li>Do not allow to enter drains or watercourses.</li> <li>Dispose of according to all federal, state and local applicable regulations.</li> <li>If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.</li> <li>For further information, contact your local waste authority.</li> </ul>
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	<ul> <li>Recycling possible. Ensure packaging is completely empty before recycling.</li> <li>Dispose of uncured residues in the same way as the product itself. Plastic articles</li> <li>15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06.</li> </ul>
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

AC001S02F103-01

#### **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not applicable. bulk according to IMO instruments

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions : Not applicable. on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

**Other EU regulations** 

Ozone depleting substances (1005/2009/EU) Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants Not listed.

**Seveso Directive** 

AC001S02F103-01

## **SECTION 15: Regulatory information**

This product is not controlled under the Seveso Directive.

15.2	Chemical	safety
2000	eemont	

- : No Chemical Safety Assessment has been carried out.
- assessment
- .

#### **SECTION 16: Other information**

Indicates information that	at has changed from previously issued version.
Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative</li> </ul>
Key literature references and sources for data	<ul> <li>Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road DPD = Dangerous Preparations Directive [1999/45/EC] DSD = Dangerous Substances Directive [67/548/EEC] IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Directive 2012/18/EU, and relative amendments &amp; additions Directive 2008/98/EC, and relative amendments &amp; additions Directive 2009/161/EU, and relative amendments &amp; additions CEPE Guidelines</li> </ul>

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification
Not classified.		
Full text of abbreviated H	: H220	Extremely flammable gas.
statements	H224	Extremely flammable liquid and vapour.
	H225	Highly flammable liquid and vapour.
	H226	Flammable liquid and vapour.
	H280	Contains gas under pressure; may explode if heated.
	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H310	Fatal in contact with skin.
	H311	Toxic in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H330	Fatal if inhaled.
	H331	Toxic if inhaled.
	H332	Harmful if inhaled.
	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H340	May cause genetic defects.
	H341	Suspected of causing genetic defects.
	H350	May cause cancer.
	H351	Suspected of causing cancer.
	H360Fd	May damage fertility. Suspected of damaging the unborn child.

AC001S02F103-01

### **SECTION 16: Other information**

SECTION 16: Other Info	ormation
	H372 Causes damage to organs through prolonged or repeated exposure.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.
	EUH019 May form explosive peroxides.
	EUH066 Repeated exposure may cause skin dryness or cracking.
	EUH071 Corrosive to the respiratory tract.
Full text of classifications	Acute Tox. 2 ACUTE TOXICITY - Category 2
[CLP/GHS]	Acute Tox. 3 ACUTE TOXICITY - Category 3 Acute Tox. 4 ACUTE TOXICITY - Category 4
	0,
	Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
	Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD -
	Category 3 Carc. 1B CARCINOGENICITY - Category 1B
	Carc. 2 CARCINOGENICITY - Category 2
	Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	Flam. Gas 1A FLAMMABLE GASES - Category 1A
	Flam. Liq. 1 FLAMMABLE LIQUIDS - Category 1
	Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
	Muta. 1B GERM CELL MUTAGENICITY - Category 1B
	Muta. 2 GERM CELL MUTAGENICITY - Category 2
	Press. Gas (Comp.) GASES UNDER PRESSURE - Compressed gas
	Repr. 1B REPRODUCTIVE TOXICITY - Category 1B
	Skin Corr. 1 SKIN CORROSION/IRRITATION - Category 1
	Skin Corr. 1A SKIN CORROSION/IRRITATION - Category 1 Skin Corr. 1A SKIN CORROSION/IRRITATION - Category 1A
	Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
	Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C
	Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
	Skin Sens. 1 SKIN SENSITISATION - Category 1
	Skin Sens. 1A SKIN SENSITISATION - Category 1A
	STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED
	EXPOSURE - Category 1
	STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	: 09, Feb, 2023.
Date of issue/ Date of revision	: 09, Feb, 2023.
Date of previous issue	: 17, Dec, 2022.
	<ul> <li>If there is no previous validation date please contact your supplier for more information.</li> </ul>
Version	: 7
Notice to reader	

AC001S02F103-01

#### **SECTION 16: Other information**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country or local laws. The conditions for use of the product are not under the control of the manufacturer, therefore the customer/buyer/ user is responsible for determining the conditions necessary for the safe use of this product. The customer/ buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.