PRODUCT DATA SHEET

EVERBUILD FOREVER WHITE® Powder Wall Tile Grout

CEMENT BASED POWDERED GROUTING COMPOUND.

PRODUCT DESCRIPTION

With Mould Shield®, one of the world's leading anti-bacterial solutions, integrated into the manufacturing process, Forever White Powder Wall Tile Grout is proven to protect against mould, mildew and bacterial growth.
Forever White Powder Wall Tile Grout is independently tested and certified by a NAMMAS accredited microbiological laboratory to show no mould growth after more than 10 Years simulated ageing. Copies of test data are available upon request.
Forever White Powder Wall Tile Grout dries to an extra brilliant white finish.
Forever White Powder Wall Tile Grout is a cement based powdered grouting compound with added PVA to promote adhesion and water repellents to shed water. Simply mix with water to give a pure white paste.

USES

- Kitchen/Bathroom walls.
- Shower areas.
- Work tops subject to water contact.

CHARACTERISTICS / ADVANTAGES

- Excellent water resistance.
- Dries brilliant white.
- Contains Mould Shield®
- Can be used on wall joints up to 3mm.
- Power-showerproof.
- Repels water.

APPROVALS / STANDARDS

Tested in accordance with EN13888 – Class CG1

PRODUCT INFORMATION

Packaging	1.2kg box and 3kg Paper Sack.
Appearance / Colour	Arctic White
Shelf Life	12 months when stored in original unopened containers
Storage Conditions	Store in cool (5 - 25°C) dry conditions. AVOID MOISTURE

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry and free from contaminants such as adhesive, paint etc. Tiles must be left for at least 24hr (3 days on non porous surfaces) for the adhesive to dry before grouting.

MIXING

Mix approximately 2 parts powder to 1 part water. Mix to a smooth lump free paste. Allow to stand 10 minutes before grouting, then re-stir.

APPLICATION

Apply by cloth or squeegee. Push grout well into joints

so no voids remain behind. Remove excess grout with a damp cloth before it dries.
Protect all grouted areas from running water and frost until the grout is completely dry.

LIMITATIONS

- Unsuitable for floors.
- Always mix with clean fresh water. Allow adhesive to dry before grouting. Protect from running water and frost until completely dry. Do not use where application would trap moisture within the substrate.
- Tiles must be left for at least 24hr (3 days on non porous surfaces) for the adhesive to dry before grouting; longer at low temperatures. Grouting too early will cause a discolouration of the grout which is normally Arctic White in colour.
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services department for advice. In all circumstances, the manufacturer’s liability is limited to the value of the manufacturer’s product purchased.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product’s suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD
Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED
Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland