



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**SX CONTRACTORS LEAD SHEET SILICONE**  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** SX CONTRACTORS LEAD SHEET SILICONE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** Consumer use  
**Reason why uses advised against** Restricted substance per REACH Annex XVII

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Siroflex Limited  
Dodworth Business Park, Dodworth  
Barnsley, South Yorkshire  
S75 3SP  
Tel: +44 (1226) 771600 Fax: +44 (1226) 771601  
www.siroflex.co.uk

**E-mail address** technical.siroflex@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1226) 771600 (Office Hours Only)  
**Ireland** **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

*Regulation (EC) No 1272/2008*

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1A - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity — single exposure	Category 2
Chronic aquatic toxicity	Category 3 - (H412)

### 2.2. Label elements

Contains 2-octyl-2H-isothiazol-3-one [OIT] & 2-Butanone, oxime & 3-aminopropyltriethoxysilane

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL



**Signal word**  
Danger

## Hazard statements

H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H350 - May cause cancer.  
H371 - May cause damage to organs.  
H412 - Harmful to aquatic life with long lasting effects.

## Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor  
P362 + P364 - Take off contaminated clothing and wash it before reuse  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

## 2.3. Other hazards

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Causes mild skin irritation. Harmful to aquatic life.

## PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	>25 - <40	Asp. Tox. 1 (H304)	-	01-2119827000-58-XXXX
Silica, amorphous	231-545-4	7631-86-9	5 - <10	[B]	-	01-2119379499-16-XXXX
2-Butanone, oxime	202-496-6	96-29-7	1- <2.5	Acute Tox. 3 (H301) Acute Tox. 4 (H312)	-	01-2119539477-28-XXXX

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

				Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)		
3-aminopropyltriethoxysilane	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	01-2119480479-24-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	[C]	-	01-2119489379-17-XXXX
Octamethylcyclotetrasiloxane [D4]	209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238-36-XXXX
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7	26530-20-1	0.0015 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.0015%	-

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

Substances identified by a number starting "RR-" in the CAS-field are substances for which there is no CAS# used in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash with soap and water. May cause an allergic skin reaction. Wash off immediately with plenty of water for at least 15 minutes. If symptoms persist, call a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

## 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	TWA/8h 5mg/m <sup>3</sup> STEL/15 mins 10mg/m <sup>3</sup>	-
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup> STEL: 0.3 mg/m <sup>3</sup>
Ethanol 64-17-5	-	TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup> STEL: 3000 ppm STEL: 5760 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**SX CONTRACTORS LEAD SHEET SILICONE**  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

		STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
--	--	--

**Derived No Effect Level (DNEL)**      No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>2-Butanone, oxime (96-29-7)</b>			

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
DNEL/DMEL Long term Systemic health effects	Inhalation	0.028 mg/m <sup>3</sup>	
Long term Local health effects	Inhalation	0.9 mg/m <sup>3</sup>	
DNEL/DMEL Long term Systemic health effects	Dermal	0.004 mg/kg bw/d	

<b>3-aminopropyltriethoxysilane (919-30-2)</b>			
--	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
--------------------------------------	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
---	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
---------------------------------------	--	--	--

<b>2-Butanone, oxime (96-29-7)</b>			
------------------------------------	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	0.00482 mg/m <sup>3</sup>	
Long term Local health effects	Dermal	0.43 mg/m <sup>3</sup>	

<b>3-aminopropyltriethoxysilane (919-30-2)</b>			
--	--	--	--

Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**SX CONTRACTORS LEAD SHEET SILICONE**  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

		(DNEL)	
Consumer Long term Systemic health effects	Inhalation	17 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

## Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

## Octamethylcyclotetrasiloxane [D4] (556-67-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

## Predicted No Effect Concentration (PNEC)

### 3-aminopropyltriethoxysilane (919-30-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

### Titanium dioxide (13463-67-7)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

### Octamethylcyclotetrasiloxane [D4] (556-67-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

## 8.2. Exposure controls

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

<b>Engineering controls</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
<b>Hand protection</b>	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.
<b>Environmental exposure controls</b>	Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid	
<b>Appearance</b>	Paste	
<b>Colour</b>	See section 1 for more information	
<b>Odour</b>	Characteristic.	
<b>Odour threshold</b>	No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 100 °C	
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	.	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	> 21 mm <sup>2</sup> /s	
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	No data available. Product cures with moisture	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Density</b>	0.96	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

<b>Solid content (%)</b>	No information available	
<b>VOC Content (%)</b>		No data available

#### 9.2.1. Information with regards to physical hazard classes

Not applicable

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

## 9.2.2. Other safety characteristics

No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

**Incompatible materials** Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation. Causes mild skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes. Prolonged contact may cause redness and irritation.

## Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 8,333.30 mg/kg  
ATEmix (dermal) 91,666.70 mg/kg

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 (Rattus)
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rat, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m <sup>3</sup> (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** May cause skin irritation. Classification based on data available for ingredients.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information  
2-Butanone, oxime (96-29-7)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Chemical name	European Union
2-Butanone, oxime	Carc. 1B

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

**STOT - single exposure** Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). May cause damage to organs.

H371 - May cause damage to the following organs: upper respiratory tract.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h) > 3193 mg/l (Acartia tonsa)		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

			applicable to inorganic substances
--	--	--	------------------------------------

Octamethylcyclotetrasiloxane [D4] (556-67-2)  
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
2-Butanone, oxime	0.65
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	The substance is not PBT / vPvB
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does not apply
2-Butanone, oxime	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

# SAFETY DATA SHEET

SX CONTRACTORS LEAD SHEET SILICONE  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

## 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	None

### IMDG

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Marine pollutant</b>	NP
<b>14.6 Special Provisions</b>	None
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	None

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# SAFETY DATA SHEET

**SX CONTRACTORS LEAD SHEET SILICONE**  
Date: 05.10.2023

Replaces: 11.05.2021  
Ref: 0421.1.BB/DL

## **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Reserved for industrial and professional use.

## **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

This product contains a biocidal product for the preservation of the dry film Contains: 2-octyl-2H-isothiazol-3-one [OIT]

## **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

## **Persistent Organic Pollutants**

Not applicable

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H361f - Suspected of damaging fertility

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

#### **Legend**

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

\*

Skin designation

# SAFETY DATA SHEET

**SX CONTRACTORS LEAD SHEET SILICONE**  
**Date: 05.10.2023**

**Replaces: 11.05.2021**  
**Ref: 0421.1.BB/DL**

---

SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 26-Jul-2022

## Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**