



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX PROFESSIONALS SOLVENT CLEANER

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Consumer use

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park, Dodworth Barnsley,
South Yorkshire S75 3SP
Tel: +44 (1226) 771600
Fax: +44 (1226) 771601 www.siroflex.co.uk

E-mail address technical.siroflex@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1226) 771600 (Office Hours Only)

Ireland

NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service) 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Aspiration hazard	Category 1 - (H304)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate, Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL



Signal word
Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
H225 - Highly flammable liquid and vapour.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P331 - Do NOT induce vomiting
P337 + P313 - If eye irritation persists: Get medical advice/attention
P391 - Collect spillage
P403 + P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Causes mild skin irritation.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008	Specific concentration limit (SCL)	REACH registration number
---------------	---------------------	--------	----------	---	------------------------------------	---------------------------

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

				[CLP]		
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	RR-100218-2	40 - <80	STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) (EUH066) Flam. Liq. 2 (H225)	-	01-2119473851-33-XXXX
n-Butyl acetate	(607-025-00-1) 204-658-1	123-86-4	20 - 25	STOT SE 3 (H336) Flam. Liq. 3 (H226) (EUH066) [B]	-	01-2119485493-29-XXXX
Ethanol	(603-002-00-5) 200-578-6	64-17-5	10 - <20	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	01-2119457610-43-XXXX
2-Butoxyethanol	(603-014-00-0) 203-905-0	111-76-2	5 - <10	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)	-	01-2119475108-36-XXXX
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	5 - <10	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)	-	01-2119458049-33-XXXX
Ethyl acetate	(607-022-00-5) 205-500-4	141-78-6	0.1 - <1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	01-2119475103-46-XXXX

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
 [B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO ₂).

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific use(s)

Consumer use.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
n-Butyl acetate 123-86-4	TWA: 241 mg/m ³ TWA: 50 ppm STEL: 723 mg/m ³ STEL: 150 ppm	TWA: 150 ppm TWA: 724 mg/m ³ STEL: 200 ppm STEL: 966 mg/m ³
Ethanol 64-17-5	-	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³
2-Butoxyethanol 111-76-2	TWA: 20 ppm TWA: 98 mg/m ³ STEL: 50 ppm STEL: 246 mg/m ³ *	TWA: 25 ppm TWA: 123 mg/m ³ STEL: 50 ppm STEL: 246 mg/m ³ Sk*
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	-	TWA: 350 mg/m ³
Ethyl acetate 141-78-6	TWA: 734 mg/m ³ TWA: 200 ppm STEL: 1468 mg/m ³ STEL: 400 ppm	TWA: 734 mg/m ³ TWA: 200 ppm STEL: 1468 mg/m ³ STEL: 400 ppm

Chemical name	European Union	Ireland	United Kingdom
2-Butoxyethanol 111-76-2	-	200 mg/g Creatinine (urine - end of shift)	240 mmol/mol creatinine urine

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

n-Butyl acetate (123-86-4)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	300 mg/m ³	
worker Short term Systemic health effects	Inhalation	600 mg/m ³	
worker	Inhalation	300 mg/m ³	

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

Long term Local health effects			
worker Short term Local health effects	Inhalation	600 mg/m ³	
worker Long term Systemic health effects	Dermal	11 mg/kg bw/d	

Ethanol (64-17-5)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	950 mg/m ³	
worker Long term Systemic health effects	Dermal	343 mg/kg bw/d	

2-Butoxyethanol (111-76-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	98 mg/m ³	
worker Systemic health effects Long term	Dermal	125 mg/kg bw/d	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	330 mg/m ³	
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d	

Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m ³	
worker Long term Local health effects	Inhalation	734 mg/m ³	
worker Short term Local health effects	Inhalation	1468 mg/m ³	
worker Long term Systemic health effects	Inhalation	734 mg/m ³	

Derived No Effect Level (DNEL)

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

n-Butyl acetate (123-86-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	300 mg/m ³	
Consumer Long term Local health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Local health effects	Inhalation	300 mg/m ³	
Consumer Long term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	2 mg/kg bw/d	

Ethanol (64-17-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	114 mg/m ³	
Consumer Long term Systemic health effects	Dermal	206 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	87 mg/kg bw/d	

2-Butoxyethanol (111-76-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	59 mg/m ³	
Consumer Systemic health effects Long term	Dermal	75 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	6,3 mg/kg bw/d	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	71 mg/m ³	
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d	

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	
--	------	---------------	--

Ethyl acetate (141-78-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m ³	
Consumer Long term Local health effects	Inhalation	367 mg/m ³	
Consumer Short term Local health effects	Inhalation	734 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	367 mg/m ³	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
n-Butyl acetate (123-86-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.18 mg/l
Marine water	0.018 mg/l
Freshwater - intermittent	0.36 mg/l
Sewage treatment plant	35.6 mg/l
Freshwater sediment	0.981 mg/l
Marine sediment	0.0981 mg/l
Soil	0.0903 mg/l

Ethanol (64-17-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	154 mg/l
Marine water	15.4 mg/l
Sewage treatment plant	100 mg/l

2-Butoxyethanol (111-76-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	8,8 mg/l
Marine water	0,88 mg/l
Sewage treatment plant	463 mg/l
Freshwater sediment	34,6 mg/kg dry weight
Marine sediment	3,46 mg/kg dry weight
Soil	2,33 mg/kg dry weight

Ethyl acetate (141-78-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.24 mg/l
Marine water	0.024 mg/l
Freshwater sediment	1.15 mg/kg
Marine sediment	0.115 mg/kg

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

Soil	0.148 mg/kg
Microorganisms in sewage treatment	650 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Colour Colourless
Odour Solvent.
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	78.4 - 115.4 °C	None known
Flammability	Not applicable for liquids	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	19	
Lower flammability or explosive limits	3.3	
Flash point	12 °C	None known
Autoignition temperature	230 °C	None known
Decomposition temperature		None known
pH	7	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	Slightly soluble.	None known
Solubility(ies)	Acetone	None known
Partition coefficient	No data available	None known
Vapour pressure	5.8	None known
Relative density	0.744	None known
Bulk Density	No data available	
Liquid Density	0.774	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	12,121.20 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	30.3030 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate	>10650 mg/kg (Rattus)	> 17600 mg/kg (Oryctolagus cuniculus)	=390 ppm (Rattus) 4 h
Ethanol	6200 - 15000 mg/kg (Rattus) OECD 401	-	=124.7 mg/L (Rattus) 4 h
2-Butoxyethanol	=1476 mg/kg (Rattus)(OECD 401)	LD 0 >2000 mg/kg (guinea pig) (OECD 402)	LC 0 (1h) > 3.1 mg/l (guinea pig)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		4 hours	Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal	0.1 mL		Product score 1 Non-irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Ethyl acetate (141-78-6)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
n-Butyl acetate 123-86-4	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50 96 h 17 - 19 mg/L (Pimephales promelas flow-through)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 48 h = 44 mg/L (Daphnia magna)		
Ethanol 64-17-5	EC50 72hr 12.9 g/l (Senastrum capricornutum) NOEC 3.24 g/l (Skeletonema costatum)	LC50: >100mg/L (96h, Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, Daphnia magna) EC50: =12.34 mg/L		
2-Butoxyethanol 111-76-2	EC50 (72h) = 1840 mg/L (Pseudokirchner iella subcapitata) OECD 201	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna) EC50: 1698 - 1940mg/L (24h, Daphnia magna)		
Hydrocarbons, C9-C12,	EL50 (72h) = 4.1	LL50 96hr 10-30	-	EL50 48hr		

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	mg/l (Pseudokirchnerella subcapitata) OECD 401	mg/l (Oncorhynchus mykiss)		10-30mg/l (daphnia magna)		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmododesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

n-Butyl acetate (123-86-4)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	83%	Readily biodegradable

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)

Method	Exposure time	Value	Results
	28 days	biodegradation	74.7 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
n-Butyl acetate	2.3
Ethanol	-0.35
2-Butoxyethanol	0.81
Ethyl acetate	0.73

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
n-Butyl acetate	The substance is not PBT / vPvB PBT assessment does not apply
Ethanol	The substance is not PBT / vPvB PBT assessment does not apply
2-Butoxyethanol	The substance is not PBT / vPvB
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	The substance is not PBT / vPvB
Ethyl acetate	The substance is not PBT / vPvB PBT assessment does

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

	not apply
--	-----------

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN1993
14.2 UN proper shipping name	Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate)
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1993, Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate), 3, II, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	274, 601, 640D
Classification code	F1
Tunnel restriction code	(D/E)
Limited quantity (LQ)	1 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN number or ID number	UN1993
14.2 UN proper shipping name	Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate)
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1993, Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate), 3, II, (12°C c.c.), Marine Pollutant
14.5 Marine pollutant	P
14.6 Special precautions for user	
Special Provisions	274
Limited Quantity (LQ)	1 L
EmS-No.	F-E, S-E
14.7 Maritime transport in bulk according to IMO instruments	

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1993
14.2 UN proper shipping name	Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate)
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1993, Flammable liquid, n.o.s. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, n-Butyl acetate), 3, II
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	A3
Limited quantity (LQ)	1 L
ERG Code	3H

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SAFETY DATA SHEET

SX PROFESSIONALS SOLVENT CLEANER
Date: 12.09.2023

Replaces: 01.12.2018
Ref: 0175.14.LS/DL

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 05-Jun-2023

Indication of changes

Revision note Not applicable.
Training Advice No information available
Further information No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet