

## Technical Data Sheet

### Product

**OB41 High Performance Silicone Lubricant Spray** is a clear, non-staining lubricant.

### Applications

**OB41 High Performance Silicone Lubricant Spray** is widely used in the furniture and bed manufacturing industries, where the cleaning and lubricating properties of silicone give excellent benefits. It is also ideal for use in textile manufacturing as a lubricant for machinery and table tops. **OB41 High Performance Silicone Lubricant Spray** provides a clear barrier which is excellent for treating machinery and moving parts against the build up of dust, hair and foreign matter. Being impervious to water, it deposits a film onto protective clothing, canvas tents, golf bags, umbrellas, fishing and camping accessories and other similar materials, making them rain and shower proof. **OB41 High Performance Silicone Lubricant Spray** puts slip where you want it, and is excellent for treating desk drawers, squeaking hinges, seized locks and is superb for lubricating tools such as saw blades and cutting edges. It puts the shine back on vehicle dashboards and door panels and may be used as a general purpose polish. **OB41 High Performance Silicone Lubricant Spray** revitalises metal zip fasteners.

**OB41 High Performance Silicone Lubricant Spray** is ideal for all mould release applications. It effectively prevents any surfaces bonding, and will not affect the surface finish of cured resins. Excellent high temperature stability means that the product is suitable for use on plastic injection moulding machines, although the product should not be sprayed onto hot surfaces, due to the flammable nature of the propellants used.

### Method of Use

Dependant upon application, **OB41 High Performance Silicone Lubricant Spray** should be sprayed onto the surface from 15cm (6 inches) to 25cm (10 inches), if required buff with a clean cloth.

### Handling and Storage Considerations

Whilst handling **OB41 High Performance Silicone Lubricant Spray**, we advise to keep away from heat, sparks and open flames and to use the aerosol in well ventilated areas. **OB41 Silicone Lubricant Spray** needs to be stored at moderate temperatures in dry, well ventilated areas and must not be exposed to direct sunlight or temperatures above 50°C.

## **Benefits**

Portable:	Lightweight 400ml Aerosol.
Ease of Use:	Spray on, wipe off.
Clean:	Every application is a clean, fresh application.
Health and safety:	It does not contain potentially environment or ozone damaging materials such as CFCs.
Shelf Life:	24 months from date of manufacture.

## **Disposal Considerations**

**OB41 High Performance Silicone Lubricant Spray** must be disposed of safely, in accordance with local authority requirements. The empty containers must not be burned due to explosion hazards.

## **Recommendations**

We recommend that you view the Safety Data Sheet (SDS) for further information on the product before use and if you have any questions or queries then you can contact technical services.

## **DISCLAIMER**

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of Siroflex Ltd is stated or implied. No employee of Siroflex Ltd has the authority to waive or alter in any way the content of this document.

Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used.

It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed.

This datasheet replaces all former versions