

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Date: 26.04.2023

Replaces:15.11.2021 Ref: 0393.3.BO/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited

Dodworth Business Park, Dodworth Barnsley,

South Yorkshire, S75 3SP

Tel: +44 (1226) 771600 Fax: +44 (1226) 771601

www.siroflex.co.uk

E-mail address info.siroflex@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1226) 771600 (Office Hours Only)
NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction

EUH210 - Safety data sheet available on request

United Kingdom - BE Page 1 / 14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

2.3. Other hazards

Combustible liquid.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Diisononyl phthalate	249-079-5	28553-12-0	5 - <10	[1]	-	01-2119430798- 28-XXXX
Ethylene glycol	(603-027-00- 1) 203-473-3	107-21-1	0.1- <1	STOT RE 2 (H373) Acute Tox. 4 (H302)	-	01-2119456816- 28-XXXX
Titanium dioxide	(022-006-00- 2) 236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379- 17-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	(613-088-00- 6) 220-120-9	2634-33-5	0.01 - < 0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]		55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691- 48-XXXX

United Kingdom - BE Page 2/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Date: 26.04.2023 Ref: 0393.3.BO/DL

Replaces:15.11.2021

	Aquatic Chronic 1	
	(H410)	

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of

contamination. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

United Kingdom - BE Page 3 / 14

[[]I] - Restricted substance per REACH Annex XVII

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Date: 26.04.2023 Ref: 0393.3.BO/DL

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Replaces:15.11.2021

chemical

Hazardous combustion products Carbon oxides.

5.3. Advice for firefighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

precautions for fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dyke

far ahead of liquid spill for later disposal. Do not scatter spilled material with high

pressure water streams.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

Do not eat, drink or smoke when using this product. Wash hands before breaks and after General hygiene considerations

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Protect from moisture. Keep away from food, drink and animal feedingstuffs. Keep from **Storage Conditions**

freezing.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C. Do not freeze.

7.3. Specific end use(s)

Specific use(s)

United Kingdom - BE Page 4/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium **Exposure Limits** dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Diisononyl phthalate	-	TWA: 5 mg/m ³
28553-12-0		STEL: 15 mg/m ³
Ethylene glycol 107-21-1	TWA: 20 ppm TWA: 52 mg/m³ STEL: 40 ppm STEL: 104 mg/m³ *	TWA: 10 mg/m³ TWA: 20 ppm TWA: 52 mg/m³ STEL: 40 ppm STEL: 104 mg/m³ STEL: 30 mg/m³ SK*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)						
Diisononyl phthalate (28553	Diisononyl phthalate (28553-12-0)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Long term Systemic health effects	Inhalation	51.72 mg/m³				
worker Long term Systemic health effects	Dermal	366 mg/kg bw/d				

Ethylene glycol (107-21-1)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d			
worker Long term Systemic health effects	Inhalation	35 mg/m ³			

Titanium dioxide (13463-67-7)					
Type	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
worker	Inhalation	10 mg/m ³			
Long term					
Local health effects					

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)						
Type	Exposure route	Derived No Effect Level	Safety factor			
	· .	(DNEL)	-			

United Kingdom - BE Page 5/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

worker	Inhalation	6.81 mg/m ³	
Long term			
Systemic health effects			
worker	Dermal	0.966 mg/kg bw/d	
Long term			
Systemic health effects			

Derived No Effect Level (DNEL)						
Ethylene glycol (107-21-1)	Ethylene glycol (107-21-1)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d				
Consumer Long term Local health effects	Inhalation	7 mg/m³				

Titanium dioxide (13463-67-7)					
Type	1	Derived No Effect Level (DNEL)	Safety factor		
Consumer	Oral	700 mg/kg bw/d			
Long term					
Systemic health effects					

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m³			
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
Ethylene glycol (107-21-1)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	10 mg/l			
Marine water	1 mg/l			
Freshwater sediment	20.9 mg/kg dry weight			
Soil	1.53 mg/kg dry weight			
Microorganisms in sewage treatment	199.5 mg/l			
Freshwater - intermittent	10 mg/l			

Titanium dioxide (13463-67-7)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Marine water	0.0184 mg/l		
Freshwater sediment	1000 mg/kg		
Freshwater	0.184 mg/l		
Marine sediment	100 mg/kg		
Soil	100 mg/kg		
Microorganisms in sewage treatment	100 mg/l		
Freshwater - intermittent	0.193 mg/l		

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)

United Kingdom - BE Page 6/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 μg/l
Marine water	0.403 μg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 μg/l
Marine sediment	4.99 μg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eve/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

> Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

> > None known

None known

None known

gloves. Gloves must conform to standard EN 374 None under normal use conditions.

Skin and body protection

In case of inadequate ventilation wear respiratory protection. Wear a respirator Respiratory protection

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Paste Colour White Odour Sweet

Odour threshold No information available

Values_ Property Remarks • Method

Melting point / freezing point 100 °C Initial boiling point and boiling

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

Flash point > 80 °C CC (closed cup) No data available None known **Autoignition temperature** None known

Decomposition temperature

8 - 9 Not applicable. pН pH (as aqueous solution) No data available None known None known

Kinematic viscosity No data available **Dvnamic viscosity** No data available Water solubility Dispersible.

Solubility(ies) Not applicable Partition coefficient No data available Vapour pressure No data available

No data available Relative density **Bulk Density** No data available

Density 1.63

Relative vapour density No data available None known

United Kingdom - BE Page 7/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Date: 26.04.2023 Ref: 0393.3.BO/DL

Replaces:15.11.2021

Particle characteristics

Particle Size No information available
Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content 0.6% 10.9g/l

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contactBased on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diisononyl phthalate	>9750 mg/kg (Rattus)	>3160 mg/Kg (Oryctolagus cuniculus)	>4.4 mg/L (Rattus) 4 h
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 μL/kg (Oryctolagus cuniculus)	> 2.5 mg/L (Rat)6 h
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
1,2-benzisothiazol-3(2H)-one [BIT]	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Thailian dioxide (10 100 07 1)					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser		
Sensitisation					
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser		
Sensitisation: Local Lymph Node					

United Kingdom - BE Page 9/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Assay

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Diisononyl phthalate	EC50: >500mg/L	LC50 96 h > 100	-	EC50: >500mg/L		
28553-12-0	(72h,	mg/L		(48h, Daphnia		
	Desmodesmus	(Brachydanio		magna)		
	subspicatus)	rerio semi-static)		EC50:		
	EC50: >1.8mg/L	,		>0.06mg/L (48h,		
	(96h,			Daphnia magna)		
	Pseudokirchneri					
	ella subcapitata)					
Ethylene glycol	EC50: 6500 -	LC50 96 h =	EC50 = 10000	EC50:		
107-21-1	13000mg/L (96h,	16000 mg/L	mg/L 16 h	=46300mg/L		
	Pseudokirchneri	(Poecilia	EC50 = 620	(48h, Daphnia		
	ella subcapitata)	reticulata static)	mg/L 30 min	magna)		
			EC50 = 620.0			
			mg/L 30 min			
Titanium dioxide	LC50 (96h)	-	-	-		
13463-67-7	>10000 mg/l					
	(Cyprinodon					
	variegatus)					
	OECD 203					
1,2-benzisothiazol-3(2	EC50 3Hr	LC50 (96hr) 2.15	-	EC50(48hr) 2.94	1	

United Kingdom - BE Page 10 / 14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Date: 26.04.2023 Ref: 0393.3.BO/DL

Replaces:15.11.2021

H)-one [BIT] 2634-33-5		mg/l Cyprinodon variegatus EPA 540/9-85-006		mg/l (Daphnia Magna) OECD 202		
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner		-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Component information		
Chemical name	Partition coefficient	
Diisononyl phthalate	9.7	
Ethylene glycol	-1.36	
1,2-benzisothiazol-3(2H)-one [BIT]	0.7	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7	
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

	•
Chemical name	PBT and vPvB assessment
Diisononyl phthalate	The substance is not PBT / vPvB PBT assessment does
	not apply
Ethylene glycol	The substance is not PBT / vPvB PBT assessment does
	not apply
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

United Kingdom - BE Page 11 / 14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

N | - 4 .. - -.. . | - 4 - - |

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1	UN number or ID number	Not regulated
14.2	Proper Shipping Name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable

None 14.6 Special Provisions

IMDG

14.1	UN number or ID number	Not regulated
14.2	Proper Shipping Name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Marine pollutant	NP

14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1	UN number or ID number	Not regulated
14.2	Proper Shipping Name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
446	Outsile Duscile Laure	Nama

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

United Kingdom - BE Page 12/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diisononyl phthalate	28553-12-0	52[a].

52. Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

United Kingdom - BE Page 13/14

SX DECORATORS PREMIUM PAINTABLE CAULK ACRYLIC 380ML

Replaces:15.11.2021 Date: 26.04.2023 Ref: 0393.3.BO/DL

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 μ m, length > 5 μ m and aspect ratio \geq 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Legend

TWA (time-weighted average) TWA **STEL** STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Skin designation

Substance(s) of Very High Concern **SVHC**

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

European Waste Catalogue **EWC**

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

International Maritime Dangerous Goods (IMDG) **IMDG** International Air Transport Association (IATA) IATA

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Product Safety & Regulatory Affairs Prepared By

Revision date 07-Feb-2023

Indication of changes

Not applicable. **Revision note**

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14/14