All-in-one Genius Spray

Revision: 2/04/2019 Page 1 from 1

Technical data

Basis	Mixture based on mineral oil
Consistency	Liquid
Density**	Ca. 0,67 g/ml
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	82 %
Temperature resistance**	-45 °C → 200 °C
Application temperature	5 °C → 30 °C

^{*} These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Genius spray allows precise extrusion and regular spray action. All-in-one Genius Spray is a high-quality universal spray with 8-fold action: rust dissolver, lubricant, cleaner, water-repellent, penetrating oil, corrosion-resistant, contact spray, shock spray.

Properties

- Lubricates
- Protects
- · Rust and corrosion-resistant
- · Reduces humidity
- Removes dirt and grease
- Cooling and shrinking effect (shock spray)
- Water-repellent
- Does not contain silicones
- For in and outdoor use
- Aerosol can be used in any angle (360°)
- Contains non flammable propellant
- High quality spray that retains it's properties long after application compared to other multisprays
- Complies to NSF H1 (Registration No. 156124)

Applications

- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...
- Is corrosion-resistant. Has a penetrating action anda protective film remains after cleaning
- Does not attack rubber, plastics or metals.
- Foodsafe, may be used in applications where incidental food contact may potentially occur

Packaging

Colour: Transparent Packaging: 300 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Nature: clean, free of dust and grease. All types of metals and plastics.

Application method

Application method: Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. Switch electric installations back on when spray is evaporated. When used as a rust dissolver, wait for 5 to 10 minutes.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. The products mentioned in Annex II of Regulation (EU) 1169/2011 are not part of our formulations and to the best of our knowledge our products do not contain these ingredients.