

## OIL & DRIVE CLEANER

**Thompson's Oil & Drive Cleaner is formulated to remove stubborn oil, grease and petrol stains from concrete, tarmac and stone surfaces. It can also be diluted for general cleaning.**



### COMPOSITION

A synergistic blend of surface active agents and other ingredients in an aqueous solution.

### PROPERTIES

Appearance – Yellow liquid.

VOC Content – Minimal (0-0.29% w/v).

Viscosity – Low.

Odour – Detergent type.

Solubility – Miscible with water.

### AREAS OF APPLICATION

Suitable for use on concrete, tarmac & stone driveways & garage floors.

### PREPARATION

Give the surface a scrub with a stiff bristle brush.

### APPLICATION

**Removing stubborn stains:** Apply the cleaner directly onto oil, grease & petrol stains. Work into the stain with a stiff bristle brush. Leave for 5 minutes on tarmac and 20 minutes on concrete & stone. Clean down the surface with water and a brush. **General cleaning:** Pour 1Ltr of cleaner into a 5Ltr bucket and fill the bucket up with water. Use a stiff bristle brush to clean the whole area. Leave to dry thoroughly.

### DRYING TIME

Surfaces should be dry in 1 hour but make sure they are completely dry before applying any protective coatings.

### COVERAGE

Thompson's Oil & Drive Cleaner will clean approximately 4m<sup>2</sup> per litre.

### CLEANING OF TOOLS

All equipment can be cleaned after use, by rinsing with plenty of water and detergent.

### IMPORTANT NOTES

- The cleaner may change the colour & appearance of your tarmac drive or pathway.
- Always test the cleaner on a small inconspicuous area first before cleaning the whole area.
- Take care when cleaning, as surfaces may become slippery when wet
- Avoid spillage onto surrounding vegetation
- Do not allow neat product to enter drains or watercourses
- PROTECT FROM FROST

### STORAGE

Ensure container is fully re-sealed after use.

Always store and transport in a secure and upright position.

Store in frost free conditions.

The shelf life of the product in sealed containers will be at least 2 years.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

### FLAMMABILITY

Non -flammable.

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

1L & 2L.

### DISPOSAL

Don't empty any left over product into drains or watercourses.

Your local authority may have special ways to get rid of waste coatings.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control.

### INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

### DATA SHEETS

Data sheets on other Thompson's products are available on request from our Technical Services Department.