## **Thompson's**®

#### PRODUCT DATA SHEET

# ONE COAT PATIO & BLOCK PAVING SEAL

Thompson's One Coat Patio & Block Paving Seal enhances the appearance of patios & protects from oil, fuel and weathering in just one coat.

#### **COMPOSITION**

Thompson's One Coat Patio & Block Paving Seal is a solution of acrylic resins in aromatic hydrocarbon solvents.

#### **PROPERTIES**

Appearance – Colourless, low viscosity liquid. VOC Content – Very High (greater than 50% w/v) Odour – Characteristic solvent type.

Flammable.

Immiscible with water.

#### AREAS OF APPLICATION

Suitable for use on Granite, limestone & sandstone block paving & flag stones.

#### PREPARATION

Make sure block paving, jointing sand and paving slabs are dry before you start. Give the surface a decent scrub with a stiff bristle brush to remove any dust or dirt. If you have any mould or algae, use some Thompson's Advanced Patio & Block Paving Cleaner. If you've got oil stains, use Thompson's Oil & Drive Cleaner. Make sure any cleaners are rinsed off the patio & it's dry before you start applying One Coat Patio & Block Paving Seal.

#### APPLICATION

For best results, use on a dry day above 10C. On cold & damp days, drying and re-coat times will take longer. Give the tin a good shake. Pour the tin into a roller tray and use a long pile roller to apply in long smooth strokes. On textured block paving, make sure any puddles are spread into dry areas. Really rough surfaces might need an extra coat.

#### COVERAGE

Thompson's One Coat Patio & Block Paving Seal will cover up to 6m<sup>2</sup> per litre.

Coverage will depend on the texture & type of surface you're coating.

#### **DRYING TIME**

Thompson's One Coat Patio & Block Paving Seal will be touch dry in 1 hour. Treated surfaces should not

be walked on until at least 4 hours after the final coat has dried.

Avoid heavy foot traffic and parking your car on to the surface for a further 24 hours. Thompson's One Coat Patio & Block Paving Seal will achieve its full hardness within a few days of application.

Dry times will vary depending on the texture & type of surface you're coating.

#### **CLEANING OF TOOLS**

All tools and equipment should be cleaned immediately after use with brush cleaner.

Remove as much product as possible from tools and equipment before washing.

#### **IMPORTANT NOTES**

- · Always read the instructions before use.
- Do not apply if air or surface temperature is below 10°C.
- Don't apply if its raining or forecast to rain.
- Thompsons One Coat Patio & Block Paving Seal dries to a satin sheen finish. The sheen level will be dependent on the type & nature of the block paving.
- The colour & appearance of block paving can change significantly with the application of Thompson's One Coat Patio & Block Paving Seal. Always test a small area first before coating the whole area.
- Caution: Surface may be slippy when wet.
- Avoid spillage onto surrounding vegetation and protect garden furniture.
- Remove any splashes whilst still wet with White Spirit.
- Always remove as much product as possible before cleaning equipment with White Spirit.

#### **STORAGE**

Store in a cool, dry, well ventilated place away from heat and sources of ignition and direct sunlight. Carefully reseal partly used containers. Do not store near foodstuffs. Protect from frost.

To avoid risk of spillage, always store and transport in a secure and upright position.

### No. 10541 March 2006



The shelf life of the product in airtight containers is at least two years.

#### **HEALTH AND SAFETY**

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

#### FLAMMABILITY

Flammable. Flash point  $\sim$ 440C.

#### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

#### SIZES

5L.

#### DISPOSAL

Don't empty any left over product into drains or watercourses.

Your local authority may have special ways to get rid of waste coatings.

#### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### DATA SHEETS

Data sheets on other Thompson's Products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Sherwin-Williams Diversified Brands Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.

Sherwin-Williams Diversified Brands Ltd. has achieved Investors in People certification, (certificate number 59586)

#### ©Sherwin-Williams Diversified Brands Ltd, Thorncliffe Park, Chapeltown, Sheffield S35 2YP

Tel: (0114) 240 9469 (Technical Services) (0114) 246 7171 (Main Switchboard) Fax: (0114) 245 5629 Email: enquiry@thompsonsweatherproofing.co.uk Web: www.thompsonsweatherproofing.co.uk

Thompsons is a Registered Trademark of the Sherwin-Williams Company. JANUARY, 2009 ISSUE 1