



## Felt Support Tray

Designed to prevent damage to roofing felt



### Use

- At the eaves of a roof to support and protect roofing felt
- For remedial work to replace worn or perished roofing felt

### Features and Benefits

- Effective, quick and easy to fit
- Improves performance of other roofing materials
- Ideal for remedial work
- Durable and totally resistant to decay
- Supplied in convenient 1.5m lengths

### Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

### Material and Colour Choice

- Extruded in UPVC
- Available in black/dark grey

### Installation Advice

- Fit on the top of the fascia board below roofing felt, allowing a 150mm overlap where pieces join
- Secure with clout nails and fold back the rear flap to rest on the rafters

### How to Order

- Measure the overall length of the eaves to be protected and divide by 1.35m to determine the number of protectors required

### Bill of Quantity

G20 Carpentry/Timber Framing/First Fixing

Clause

900^ EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: [www.timloc.co.uk](http://www.timloc.co.uk)
- Product Reference: 3017
- Type: Protector (1500mm)
- Colour: Black

### Product Codes

Description	Pack Quantity	Product Code
Felt support tray 1500mm	10	3017
Felt support tray 600mm	20	1128

### Product Dimensions

3017

