





# **RTV-IP** | Interlocking Plain Roof Tile Vent

Interlocking Plain roof tile vent to enable ventilation directly into a roof space or connect to a ducted ventilation system

### Uses

- On roofs with Interlocking Plain profile roof tiles
- Enables ventilation directly into a roof space
- Can also be connected to a ducted ventilation system inside the building

### **Features and Benefits**

- Suitable for roofs with a minimum pitch of 22.5°
- Free ventilation area of 6,000mm<sup>2</sup>
- Sized to replace one Interlocking Plain tile to provide a continuous visual appearance along the roof when viewed at all levels
- Shaped to manage and channel rainwater back down onto the roof tiles and away from the vent opening
- 4mm spaced external grille to prevent rainwater ingress and keep out large insects, vermin and debris
- UV stabilised top for continuous exposure to sunlight
- Lightweight and easy to handle

### **Relevant Standards**

- BS EN 490:2011 Concrete roofing tiles and fittings for roof covering and wall cladding product specifications (+A1:2017)
- BS 5250: 2021 Management of moisture in buildings Code of practice
- BS 5534:2014 Slating and tiling for pitched roofs and vertical cladding code of practice (+A2:2018)
- Manufactured to BS EN ISO 9001:2015 and BS EN ISO 14001:2015
- Complies with all relevant sections of the Building Regulations 2010
- Satisfies all relevant NHBC requirements

# Compatibility

Interlocking Plain tiles from all major manufacturers including:

- Marley Ashmore
- Redland Duoplain
- Forticrete Gemini





Terracotta RTV-IPTF Brown RTV-IPBR

Grey RTV-IPGR Red RTV-IPRD


# Material and Colour Choice


• Top - UV stabilised coloured injection moulded Polypropylene with textured finish

NB. RTV-IP available in single, pack or pallet quantities. For pack quantities, 12

- Available in Terracotta, Brown, Grey and Red
- Base Black injection moulded Polypropylene

# **Product Dimensions**





Top Profile

tile vent assemblies are packaged in one large box.

Side Profile

# **Product Codes**

| Product Description               | Colour     | Weight | Box Quantity | <b>Product Code</b> | Pack Quantity | Pack Code     | Pallet Quantity |
|-----------------------------------|------------|--------|--------------|---------------------|---------------|---------------|-----------------|
| Interlocking Plain Roof Tile Vent | Terracotta | 0.59kg | 1            | RTV-IPTE            | 12            | RTVMULTI-IPTE | 204             |
| Interlocking Plain Roof Tile Vent | Brown      | 0.59kg | 1            | RTV-IPBR            | 12            | RTVMULTI-IPBR | 204             |
| Interlocking Plain Roof Tile Vent | Grey       | 0.59kg | 1            | RTV-IPGR            | 12            | RTVMULTI-IPGR | 204             |
| Interlocking Plain Roof Tile Vent | Red        | 0.59kg | 1            | RTV-IPRD            | 12            | RTVMULTI-IPRD | 204             |

### **Accessories**

- The 110mm Flexipipe (RTV-KIT1) can be used to aid connection to ventilation duct or soil vent pipe
- The plain adapter (RTV-ADP) can be used to attach the roof tile vent to 110mm ductwork
- Can be connected to 100/110/125/150mm duct sizes when combined with the multi adapter (RTV-ADMULTI
- RTV-ADP and RTV-KIT1 available as one kit (RTV-KIT3).
  See 110mm Flevi-Pine Kits datasheet



Plain Adapter RTV-ADP





Multi Adapter RTV-ADMULTI

110mm Flexipipe RTV-KIT1

